

UPM1H820MPD

UPM1H820MPD Information

www.thesener.com	Part Number Manufacturer Category Description Package	Capacitors Aluminum Electrolytic Capacitors CAP ALUM 82UF 20% 50V RADIAL Radial, Can For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UPM1H820MPD Specifications

ManufacturerNichiconCapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPMCapacitance\$2µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature>55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance170 mOhmsLied Spacing0.138" (3.50mm)Size / Dimension0.50°T (16.50mm)Size / Dimension6.650°T (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKaial, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPMCapacitance82µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance170 mOhmsLifed Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Package / CaseRatial, Can	Manufacturer Part Number	UPM1H820MPD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPMCapacitance82µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplications320mA @ 120HzRipple Current - Low Frequency-Impedance170 mOhmsLad Spacing0.138° (3.50mm)Size / Dimension0.50° (16.50mm)Stráce Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUPMCapacitance82µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplications320mA @ 120HzRipple Current - High Frequency0.138" (3.50mm)Liad Spacing0.138" (3.50mm)Size / Dimension0.50°C (16.50mm)Size / Dimension-Mounting Type-Package / CaseMail, Can	Category	Capacitors
SeriesUPMCapacitance82µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency320mA @ 120HzInpedance170 mOhnsLead Spacing0.138° (3.50mm)Size / Dimension0.550° (16.50mm)Birghe Seated (Max)0.650° (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can		Aluminum Electrolytic Capacitors
Capacitance82µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance170 mOhmsLead Spacing0.315" Dia (8.00mm)Size / Dimension0.650" (16.50mm)Beight - Seated (Max)-Mounting TypeThrough HolePackage / CaseRidal, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarrigationPolarApplicationsGeneral PurposeRipple Current - Low Frequency320mA @ 120HzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.650" (16.50mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Package / CaseRatial, Can	Series	UPM
Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency320mA @ 120HzImpedance170 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.550" (16.50mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Capacitance	82µF
Composition-ESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency320mA @ 120HzRipple Current - High Frequency-Impedance170 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeRadial, Can	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency320mA @ 120HzRipple Current - High Frequency-Impedance170 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.650" (16.50mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	50V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency320mA @ 120HzRipple Current - High Frequency-Impedance170 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency320mA @ 120HzRipple Current - High Frequency-Impedance170 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency320mA @ 120HzRipple Current - High Frequency-Impedance170 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency320mA @ 120HzRipple Current - High Frequency-Impedance170 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of the second secon	Applications	General Purpose
Impedance170 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	320mA @ 120Hz
IILead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	170 mOhms
Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.138" (3.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.315" Dia (8.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.650" (16.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UPM1H820MPD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UPM1H820MPD Payment Methods



UPM1H820MPD Shipping Methods



If you have any question about UPM1H820MPD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com