

UPM1H820MPD6

UPM1H820MPD6 Information

www.eisener.com	Part Number Manufacturer Category Description Package	UPM1H820MPD6 Nichicon Capacitors Aluminum Electrolytic Capacitors CAP ALUM 82UF 20% 50V RADIAL Radial, Can For the pricing/inventory/lead time, please contact	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UPM1H820MPD6 Specifications

Manufacturer Nichicon Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series UPM Capacitance 82µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature 55°C ~ 105°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency - Impedance 180 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.571" (14.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPMCapacitance82µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency340mA @ 120HzImpedance1.917" (5.00mm)Size / Dimension0.934" Dia (10.00mm)Height - Seated (Max)0.571" (14.50mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRadial, Can	Manufacturer Part Number	UPM1H820MPD6
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPMCapacitance82µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplications340mA @ 120HzRipple Current - High Frequency-Impedance0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Size / Dimension0.571" (14.50mm)Height - Seated (Max)0.571" (14.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUPMCapacitance82µFTolerance-20%Voltage - Rated50VESR (Equivalent Series Resistance)-Jifetime @ Temp.5000 Hrs @ 105°COperating Temperature6000 Hrs @ 105°CPolarationPolarApplicationsGeneral PurposeRipple Current - Low Frequency340mA @ 120HzRipple Current - High Frequency0.197" (5.00mm)Siz / Dimension0.394" Dia (10.00mm)Siz / Dimension0.57" (14.50mm)Sirface Mount Land Size-Mounting TypeFlorage HolePackage / CaseRadial, Can	Category	Capacitors
SeriesUPMCapacitance82µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance180 mOhmsLied Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Bight - Seated (Max)-Surface Mount Land Size-Mounting Type-Pokaseg / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance82µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance180 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.591" (14.50mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeRatial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency340mA @ 120HzImpedance180 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.571" (14.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Series	UPM
Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency340mA @ 120HzImpedance180 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.571" (14.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Capacitance	82µF
Constraint-ESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency340mA @ 120HzRipple Current - High Frequency-Impedance180 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency340mA @ 120HzRipple Current - High Frequency-Impedance180 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.571" (14.50mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadial, Can	Voltage - Rated	50V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency340mA @ 120HzRipple Current - High Frequency-Impedance180 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.594" Dia (10.00mm)Height - Seated (Max)0.571" (14.50mm)Surface Mount Land Size-Mounting TypeFhough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency340mA @ 120HzRipple Current - High Frequency-Impedance180 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.571" (14.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency340mA @ 120HzRipple Current - High Frequency-Impedance180 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.571" (14.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
AARipple Current - Low Frequency340mA @ 120HzRipple Current - High Frequency-Impedance180 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.571" (14.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance180 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.571" (14.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	340mA @ 120Hz
IILead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.571" (14.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.571" (14.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	180 mOhms
Height - Seated (Max)0.571" (14.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.571" (14.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors'	Package / Case	Radial, Can
		Report errors?

UPM1H820MPD6 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UPM1H820MPD6 Payment Methods





If you have any question about UPM1H820MPD6, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com