

# UPM1K151MPD

#### **UPM1K151MPD Information**

www.netsteler.com	Part Number Manufacturer Category Description Package	UPM1K151MPD Nichicon Capacitors Aluminum Electrolytic Capacitors CAP ALUM 150UF 20% 80V RADIAL Radial, Can For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **UPM1K151MPD Specifications**

Manufacturer Part NumberUPM1K151MPDManufacturerNichiconCategoryCapacitorsCategoryCapacitorsPackageRadial, CanPackageSeriesCapacitance150µFCapacitance20%Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature655°C - 105°CPolarizationRediral PurposeApplicationsGeneral PurposeRipple Current - High Frequency655mA @ 104HzImpedance150mOhmsLad Spacing1.319°(3.50mm)Size / Dimension.319°(3.50mm)Mounting Type-Mounting TypeRadial, CanPolarize CharterManufacture ManufactureSurface Mount Land Size-Mounting TypeManufactureMounting TypeManufacturePaceManufacturePaceManufactureMounting TypeManufacturePaceManufacturePaceManufacturePaceManufacturePaceManufactureMounting TypeManufacturePaceManufacturePaceManufactureMounting TypeManufacturePaceManufacturePaceManufacturePaceManufacturePaceManufacturePaceManufacturePaceManufacturePaceManufacturePace<	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPMCapacitance150µFTolerance±20%Voltage - Rated80VESR (Equivalent Series Resistance)-Operating Temperature5000 Hrs @ 105°COperating Temperature65rc ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency655mA @ 100HrsInpedance150 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (1.00mm)Hight - Seated (Max).131" (33.50mm)Munting TypeFrequencyPackage / CaseRadial, Can	Manufacturer Part Number	UPM1K151MPD
Auminum Electrolytic CapacitorsPackageRadial, CanSeriesUPMCapacitance150µFTolerance±20%Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency655mA @ 120HzRipple Current - High Frequency55°MA @ 10kHzImpedance150 mOhmsLead Spacing0.197° (5.00mm)Size / Dimension3.34° Dia (10.00mm)Height - Seated (Max)1.319° (33.50mm)Surface Mount Land Size-Pokage / CaseKadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUPMCapacitance150µFTolerance=20%Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplications665mA @ 120HzRipple Current - High Frequency655mA @ 10HzImpedance150 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Size / Dimension1.319" (3.350mm)Surface Mount Land Size-Mounting TypeFincuga HolePackage / CaseRadial, Can	Category	Capacitors
SeriesUPMCapacitance150µFTolerance±20%Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency665mA @ 120HzInpedance150 mOhmsSize / Dimension0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Sirface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can		Aluminum Electrolytic Capacitors
Capacitance150µFTolerance±20%Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency655mA @ 120HzImpedance150 mOhmsStack J Spacing0.197°(5.00mm)Sizer J Dimension0.394° Dia (10.00mm)Starface Mount Land Size-Mounting TypeFrequencyPackage / CaseKadia LCan	Package	Radial, Can
Tolerance±0%Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency665mA @ 120HzImpedance150 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Series	UPM
Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency665mA @ 120HzImpedance150 mOhmsInpedance0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can	Capacitance	150µF
EV-ESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency665mA @ 120HzRipple Current - High Frequency955mA @ 10kHzImpedance150 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension1.319" (33.50mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency665mA @ 120HzNippe Current - High Frequency955mA @ 10kHzImpedance150 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can	Voltage - Rated	80V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency665mA @ 120HzRipple Current - High Frequency955mA @ 10kHzImpedance150 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeFackage / CaseRational Content - State Content - Stat	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency665mA @ 120HzRipple Current - High Frequency955mA @ 10kHzImpedance150 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency665mA @ 120HzRipple Current - High Frequency955mA @ 10kHzImpedance150 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency665mA @ 120HzRipple Current - High Frequency955mA @ 10kHzImpedance150 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
InInRipple Current - High Frequency955mA @ 10kHzImpedance150 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance150 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	665mA @ 120Hz
IILead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	955mA @ 10kHz
Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	150 mOhms
Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.319" (33.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report erro	Package / Case	Radial, Can
		Report errors?

#### **UPM1K151MPD** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **UPM1K151MPD** Payment Methods



### **UPM1K151MPD Shipping Methods**



If you have any question about UPM1K151MPD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com