

UPM1V820MED

UPM1V820MED Information

| | www.huisener.com | Part Number Manufacturer Category Description Package | Capacitors Aluminum Electrolytic Capacitors CAP ALUM 82UF 20% 35V RADIAL Radial, Can For the pricing/inventory/lead time, please contact | |
|--|--------------------|---|--|-----------------|
| | For Reference Only | | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UPM1V820MED Specifications

| ManufacturerNichiconCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPMCapacitance\$2µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature90arApplicationsGeneral PurposeRiple Current - Low Frequency265mA @ 120HzRipple Current - High Frequency190 mOhmsLifedine Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can | - | |
|--|------------------------------------|----------------------------------|
| CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageUPMCapacitance82µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature9olarApplicationsGeneral PurposeRipple Current - Low Frequency65mA @ 120HzRipple Current - High Frequency109 mOhmsLied Spacing0.098° (2.50mm)Size / Dimension0.248° Dia (6.30mm)Height - Seated (Max)0.650° (16.50mm)Surface Mount Land Size-Package / CaseRadial, Can | Manufacturer Part Number | UPM1V820MED |
| Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPMCapacitance82µFTolerance±20%Voltage - RatedSvESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency415mA @ 10kHzImpedance190 mOhmsLad Spacing0.098" (2.50mm)Siz / Dimension0.520" (16.50mm)Siz / Dimension0.650" (16.50mm)Surface Mount Land Size-Package / CaseRadial, Can | Manufacturer | Nichicon |
| PackageRadial, CanSeriesUPMCapacitance82µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolariPolarApplicationsGeneral PurposeRipple Current - Low Frequency65mA @ 120HzImpedance190 mOhmsLad Spacing0.098" (2.50mm)Siz / Dimension0.650" (16.50mm)Sirface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can | Category | Capacitors |
| SeriesUPMCapacitance82μFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency265mA @ 120HzImpedance190 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can | | Aluminum Electrolytic Capacitors |
| Capacitance82µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency265mA @ 120HzImpedance190 mOhmsLead Spacing0.098° (2.50mm)Size / Dimension0.48° Dia (6.30mm)Height - Seated (Max)0.650° (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Package | Radial, Can |
| Tolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarrPolarApplicationsGeneral PurposeRipple Current - Low Frequency265mA @ 120HzImpedance190 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.50°T (16.50mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Pokage / CaseRatial, Can | Series | UPM |
| Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency265mA @ 120HzImpedance190 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Pockage / CaseRadial, Can | Capacitance | 82µF |
| ESR-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency265mA @ 120HzMippedance190 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Tolerance | ±20% |
| Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency265mA @ 120HzMippedance190 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Voltage - Rated | 35V |
| Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency265mA @ 120HzRipple Current - High Frequency415mA @ 10kHzImpedance190 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | ESR (Equivalent Series Resistance) | - |
| PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency265mA @ 120HzRipple Current - High Frequency415mA @ 10kHzImpedance190 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Lifetime @ Temp. | 2000 Hrs @ 105°C |
| ApplicationsGeneral PurposeRipple Current - Low Frequency265mA @ 120HzRipple Current - High Frequency415mA @ 10kHzImpedance190 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Operating Temperature | -55°C ~ 105°C |
| AARipple Current - Low Frequency265mA @ 120HzRipple Current - High Frequency415mA @ 10kHzImpedance190 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Polarization | Polar |
| In PropositionAnswerRipple Current - High Frequency415mA @ 10kHzImpedance190 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Applications | General Purpose |
| Impedance190 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Ripple Current - Low Frequency | 265mA @ 120Hz |
| Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Ripple Current - High Frequency | 415mA @ 10kHz |
| Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Impedance | 190 mOhms |
| Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Lead Spacing | 0.098" (2.50mm) |
| Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can | Size / Dimension | 0.248" Dia (6.30mm) |
| Mounting TypeThrough HolePackage / CaseRadial, Can | Height - Seated (Max) | 0.650" (16.50mm) |
| Package / Case Radial, Can | Surface Mount Land Size | - |
| | Mounting Type | Through Hole |
| Report errors? | Package / Case | Radial, Can |
| | | Report errors? |

UPM1V820MED Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UPM1V820MED Payment Methods



UPM1V820MED Shipping Methods



If you have any question about UPM1V820MED, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com