

UPM2A120MED

UPM2A120MED Information

For Reference Only	Part Number	UPM2A120MED	
	Manufacturer	Nichicon	▕▋▞▔▓▐▋
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 12UF 20% 100V RADIAL	- 63.365F.
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UPM2A120MED Specifications

ManufacturerNichiconCapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPMCapacitance12µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency150mA @ 10kHzImpedance100msLied Spacing0.098° (2.50mm)Size / Dimension0.492° (12.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageRadial, CanSeriesUPMCapacitance12µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency150mA @ 120HzRipple Current - High Frequency150mA @ 10kHzImpedance0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer Part Number	UPM2A120MED
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPMCapacitance12µFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency150mA @ 10kHzImpedance1 OhmsLad Spacing0.98° (2.50mm)Size / Dimension0.44° Dia (6.30mm)Size / Dimension0.492° (12.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUPMCapacitance12µFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency55°M @ 120HZRipple Current - High Frequency150mA @ 10kHZImpedance0.098° (2.50mm)Size / Dimension0.248° Dia (6.30mm)Size / Dimension0.492° (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesUPMCapacitance12µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency75mA @ 120HzRipple Current - High Frequency100msSize / Dimension0.098" (2.50mm)Size / Dimension0.442" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Package / CaseRadial, Can		Aluminum Electrolytic Capacitors
Capacitance12µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency150mA @ 10kHzImpedance10hmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)-Surface Mount Land Size-Package / CaseKadial, Can	Package	Radial, Can
Tolerance±0%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency75mA @ 120HzImpedance1 OhmsLead Spacing0.098" (2.50mm)Size / Dimension0.442" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Package / CaseRatial, Can	Series	UPM
Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency75mA @ 120HzImpedance10hmsLead Spacing0.098" (2.50mm)Size / Dimension0.492" (12.50mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Capacitance	12µF
Constraint-ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency75mA @ 120HzImpedance10hmsLead Spacing0.098" (2.50mm)Size / Dimension0.492" (12.50mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency75mA @ 120HzRipple Current - High Frequency150mA @ 10kHzImpedance1 OhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	100V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency75mA @ 120HzRipple Current - High Frequency150mA @ 10kHzImpedance1 OhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max).492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency75mA @ 120HzRipple Current - High Frequency150mA @ 10kHzImpedance1 OhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency75mA @ 120HzRipple Current - High Frequency150mA @ 10kHzImpedance1 OhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency75mA @ 120HzRipple Current - High Frequency150mA @ 10kHzImpedance1 OhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance1 OhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	75mA @ 120Hz
Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	150mA @ 10kHz
Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	1 Ohms
Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.248" Dia (6.30mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.492" (12.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UPM2A120MED Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UPM2A120MED Payment Methods



UPM2A120MED Shipping Methods



If you have any question about UPM2A120MED, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com