

UPM2E4R7MPD

UPM2E4R7MPD Information

	Part Number	UPM2E4R7MPD	
www.crisaner.com			
	Manufacturer	Nichicon	I∎I∓ ZKI∎I
	Category	Capacitors Aluminum Electrolytic Capacitors	724
	Description	CAP ALUM 4.7UF 20% 250V RADIAL	
	Package	Radial, Can	
11		For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UPM2E4R7MPD Specifications

CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPMCapacitance4.7µFTolerance±20%Voltage - RatedSoVESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature9olarApplicationsGeneral PurposeRipple Current - Low Frequency60mA @ 120HzRipple Current - High Frequency96mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Pokage / CaseMain Qia Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPMCapacitance4.7µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature9olarApplicationsGeneral PurposeRipple Current - High Frequency60mA @ 120HzNipple Current - High Frequency96mA @ 10kHzImpedance-Lied Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm, 10.000m)Height - Seated (Max)0.669" (17.00mm, 10.000m)Surface Mount Land Size-Pokage / CaseMain Qual Main Qua	Manufacturer Part Number	UPM2E4R7MPD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPMCapacitance4.7µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency60mA @ 120HzImpedance-Lad Spacing0.197° (5.00mm)Size / Dimension0.394" Dia (10.00mm)Size / Dimension0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUPMCapacitance4.7µFTolerance20%Voltage - Rated250VESR (Equivalent Series Resistance)-Operating Temperature5000 Hrs @ 105°COperating Temperature6000 Hrs @ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency60mA @ 100HzImpedance-Lad Spacing0.197" (5.00mm)Siz / Dimension0.69" (17.00mm)Siz / Dimension0.69" (17.00mm)Surface Mount Land Size-Mounting TypeHolePackage / CaseKalial, Can	Category	Capacitors
SeriesUPMCapacitance4.7µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency60mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance4.7µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency60mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency60mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.669" (17.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	UPM
Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency60mA @ 120HzMendance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Capacitance	4.7μF
LocESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency60mA @ 120HzMippedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency60mA @ 120HzBippe Current - High Frequency96mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.669" (17.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	250V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency60mA @ 120HzBipple Current - High Frequency96mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeFuncePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency60mA @ 120HzRipple Current - High Frequency96mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency60mA @ 120HzRipple Current - High Frequency96mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40° C ~ 105° C
Ripple Current - Low Frequency60mA @ 120HzRipple Current - High Frequency96mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeFnrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	60mA @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	96mA @ 10kHz
Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.669" (17.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UPM2E4R7MPD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UPM2E4R7MPD Payment Methods



UPM2E4R7MPD Shipping Methods



If you have any question about UPM2E4R7MPD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com