

# UPS0J153MHD

Request a Quote

#### **UPS0J153MHD** Information

	Part Number	UPS0J153MHD	
STATE.	Manufacturer	Nichicon	
www.helsener.com	Category	Capacitors Aluminum Electrolytic Capacitors	
1.8	Description	CAP ALUM 15000UF 20% 6.3V RADIAL	
	Package	Radial, Can	
. /		For the pricing/inventory/lead time, please contact	
		us	
For Reference Only		Website: https://www.heisener.com	
Tor Reference Only		E-mail: salesdept@heisener.com	

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **UPS0J153MHD Specifications**

Manufacturer Part NumberUPS0J153MHDManufacturer ANichiconCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanScriesUPSCapacitance15000µFTolerance20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime Temp.3000 Hrs @ 105°COperating Temperature90aApplications6.5°C ~ 105°CPolarizationGeneral PurposeApple Current - High Frequency3.434 A @ 120HzLipedance3.00 MinsLipedance3.00 MinsLipedance4.00 MinsLipedance4.00 MinsLipedance4.00 MinsLipedance4.00 MinsLipedance4.00 MinsLipedance4.00 MinsLipedance4.00 MinsLipedance4.00 MinsLiped	-	
CategoryCapacitorsAluminum Electrolytic CapacitonsPackageRadial, CanSeriesUPSCapacitance1500µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency3.349A @ 120HzImpedance0.295° (7.50mn)Liad Spacing0.295° (7.50mn)Size / Dimension1.398° (35.50mm)Height - Seated (Max).398° (35.50mm)Surface Mount Land Size-Mounting TypeFirough HolePackage / CaseKadia, Can	Manufacturer Part Number	UPS0J153MHD
AckageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPSCapacitance15000µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency2.349A @ 120HzImpedance30 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension1.398" (35.50mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Anduning TypeRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUPSCapacitance15000µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplications2.349A @ 120HzRipple Current - High Frequency30 mOhmsLied Spacing0.295° (7.50mm)Size / Dimension1.398° (35.50mm)Size / Dimension1.398° (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesUPSCapacitance1500µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRippe Current - Low Frequency2.349A @ 120HzImpedance300 OhmsLiad Spacing0.295°(7.50mn)Size / Dimension1.398°(35.50mn)Height - Seated (Max)3.98°(35.50mn)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can		Aluminum Electrolytic Capacitors
Capacitance15000µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency2.349A @ 120HzImpedance30 mOhmsLiad Spacing0.295° (7.50mm)Size / Dimension1.398° (35.50mm)Height - Seated (Max).308° (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.349A @ 120HzImpedance30 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Hounting TypeRadial, Can	Series	UPS
Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.349A @ 120HzImpedance30 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	15000µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.349A @ 120HzImpedance30 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.349A @ 120HzRipple Current - High Frequency0.7A @ 100kHzImpedance30 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	6.3V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.349A @ 120HzRipple Current - High Frequency0.7A @ 100kHzImpedance30 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.349A @ 120HzRipple Current - High Frequency2.7A @ 100kHzImpedance30 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.349A @ 120HzRipple Current - High Frequency2.7A @ 100kHzImpedance30 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency2.349A @ 120HzRipple Current - High Frequency2.7A @ 100kHzImpedance30 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In Provide A 100Ripple Current - High Frequency2.7A @ 100kHzImpedance30 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance30 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	2.349A @ 120Hz
Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	2.7A @ 100kHz
Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	30 mOhms
Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.709" Dia (18.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.398" (35.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### **UPS0J153MHD** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **UPS0J153MHD** Payment Methods



### **UPS0J153MHD Shipping Methods**



If you have any question about UPS0J153MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com