



## **UPS2C220MPD Information**



For Reference Only

Part Number UPS2C220MPD

Manufacturer Nichicon Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 22UF 20% 160V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **UPS2C220MPD Specifications**

Manufacturer Part Number         UPS2C220MPD           Manufacturer         Nichicon           Category         Capacitors           Package         Radial, Can           Series         UPS           Capacitance         22µF           Tolerance         ±20%           Voltage - Rated         160V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         General Purpose           Ripple Current - Low Frequency         130mA @ 120Hz           Ripple Current - High Frequency         208mA @ 10kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.394" Dia (10.00mm)           Height - Seated (Max)         0.866" (22.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		
Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can           Series         UPS           Capacitance         22µF           Tolerance         ±20%           Voltage - Rated         160V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         130mA @ 120Hz           Ripple Current - High Frequency         208mA @ 10kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.394" Dia (10.00mm)           Height - Seated (Max)         0.866" (22.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer Part Number	UPS2C220MPD
Package         Radial, Can           Series         UPS           Capacitance         22µF           Tolerance         ±20%           Voltage - Rated         160V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         130mA @ 120Hz           Ripple Current - High Frequency         208mA @ 10kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.394" Dia (10.00mm)           Height - Seated (Max)         0.866" (22.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer	Nichicon
Package         Radial, Can           Series         UPS           Capacitance         22μF           Tolerance         ±20%           Voltage - Rated         160V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         130mA @ 120Hz           Ripple Current - High Frequency         208mA @ 10kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.394" Dia (10.00mm)           Height - Seated (Max)         0.866" (22.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Category	Capacitors
Series         UPS           Capacitance         22μF           Tolerance         ±20%           Voltage - Rated         160V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         130mA @ 120Hz           Ripple Current - High Frequency         208mA @ 10kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.394" Dia (10.00mm)           Height - Seated (Max)         0.866" (22.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		Aluminum Electrolytic Capacitors
Capacitance         22µF           Tolerance         ±20%           Voltage - Rated         160V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         130mA @ 120Hz           Ripple Current - High Frequency         208mA @ 10kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.394" Dia (10.00mm)           Height - Seated (Max)         0.866" (22.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 160V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose Ripple Current - Low Frequency 130mA @ 120Hz Ripple Current - High Frequency 208mA @ 10kHz  Impedance - Lead Spacing 0.197" (5.00mm)  Size / Dimension 0.394" Dia (10.00mm)  Height - Seated (Max) 0.866" (22.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Series	UPS
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 105°C  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  208mA @ 120Hz  Impedance  -  Lead Spacing  0.197" (5.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  160V  2000 Hrs @ 105°C  -40°C ~	Capacitance	22μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 105°C  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  130mA @ 120Hz  Ripple Current - High Frequency  208mA @ 10kHz  Impedance  -  Lead Spacing  0.197" (5.00mm)  Size / Dimension  0.394" Dia (10.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 105°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  208mA @ 120Hz  Impedance  -  Lead Spacing  0.197" (5.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  2000 Hrs @ 105°C  -40°C ~ 105°C  -40°C  -40°C ~ 105°C  -40°C  -40	Voltage - Rated	160V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 130mA @ 120Hz Ripple Current - High Frequency 208mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 130mA @ 120Hz  Ripple Current - High Frequency 208mA @ 10kHz  Impedance -  Lead Spacing 0.197" (5.00mm)  Size / Dimension 0.394" Dia (10.00mm)  Height - Seated (Max) 0.866" (22.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 130mA @ 120Hz Ripple Current - High Frequency 208mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency 208mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency  Impedance  Lead Spacing  O.197" (5.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  208mA @ 10kHz  -  0.197" (5.00mm)  0.394" Dia (10.00mm)  -  Through Hole  Radial, Can	Applications	General Purpose
Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	130mA @ 120Hz
Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	208mA @ 10kHz
Size / Dimension 0.394" Dia (10.00mm)  Height - Seated (Max) 0.866" (22.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.866" (22.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### **UPS2C220MPD Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **UPS2C220MPD Payment Methods**



















## **UPS2C220MPD Shipping Methods**













If you have any question about UPS2C220MPD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com