

UPS2D3R3MPD

UPS2D3R3MPD Information

www.neisener.com	Part Number Manufacturer Category Description Package	UPS2D3R3MPD Nichicon Capacitors Aluminum Electrolytic Capacitors CAP ALUM 3.3UF 20% 200V RADIAL Radial, Can For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UPS2D3R3MPD Specifications

ManufacturerNichiconCapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanStriesUPSCapacitance3.3µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeFhough HolePackage / CaseKaila, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPSCapacitance3.3µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature9olarApplicationsGeneral PurposeRipple Current - Low Frequency36mA @ 120HzRipple Current - High Frequency-Lied Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)5.12" (13.00mm)Surface Mount Land Size-Package / CaseMain, Can	Manufacturer Part Number	UPS2D3R3MPD
Aluminum Electrolytic CapacitorsPackageRadial, CanStriesUPSCapacitance3.3µFTolerance200%Voltage - Rated000 VESR (Equivalent Series Resistance)-Operating Temperature2000 Hrs @ 105°COperating Temperature600 Hrs @ 010°CPolarization60 arcal PurposeApplicationsGeneral PurposeRipple Current - High Frequency6Impedance-Lad Spacing0.138° (3.50mm)Siz / Dimension0.512° (13.00mm)Hight - Seated (Max)0.512° (13.00mm)Surface Mount Land Size-Polaring TypeRipole MathematicaPolaring Type-Surface Mount Land Size-Package / CaseMaila, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUPSCapacitance3.3µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lad Spacing0.138" (3.50mm)Size / Dimension0.512" (13.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Category	Capacitors
SeriesUPSCapacitance3.3µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency36mA @ 120HzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance3.3µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Package	Radial, Can
Toterance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarrPolarPolarizationGeneral PurposeRipple Current - Low Frequency36mA @ 120HzRipple Current - High Frequency-Lead Spacing0.138" (3.50mm)Size / Dimension0.512" (13.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	UPS
Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency36mA @ 120HzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.512" (13.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeRatial, Can	Capacitance	3.3µF
Construction-ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarPolarApplicationsGeneral PurposeRipple Current - Low Frequency36mA @ 120HzMippedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.512" (13.00mm)Height - Seated (Max)5.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency36mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.512" (13.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeRadial, Can	Voltage - Rated	200V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency36mA @ 120HzBipple Current - High Frequency-Impedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency36mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency36mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency36mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In PropositionInternational of the second secon	Applications	General Purpose
Impedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	36mA @ 120Hz
Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.138" (3.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.315" Dia (8.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.512" (13.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UPS2D3R3MPD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UPS2D3R3MPD Payment Methods



UPS2D3R3MPD Shipping Methods



If you have any question about UPS2D3R3MPD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com