



UPS2V010MPD Information



For Reference Only

Part Number UPS2V010MPD

Manufacturer Nichicon Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 1UF 20% 350V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UPS2V010MPD Specifications

Manufacturer Part Number UPS2V010MPD Manufacturer Nichicon Category Capacitors Package Aluminum Electrolytic Capacitors Package Radial, Can Series UPS Capacitance 1μF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) - ESR (Equivalent Series Resistance) 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization General Purpose Ripple Current - Low Frequency 17mA @ 120Hz Ripple Current - High Frequency 27.2mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series UPS Capacitance 1µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 17mA @ 120Hz Ripple Current - High Frequency 27.2mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	UPS2V010MPD
PackageRadial, CanSeriesUPSCapacitance1μFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency17mA @ 120HzRipple Current - High Frequency27.2mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	Nichicon
Package Radial, Can Series UPS Capacitance 1μF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 17mA @ 120Hz Ripple Current - High Frequency 27.2mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series UPS Capacitance 1µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 17mA @ 120Hz Ripple Current - High Frequency 27.2mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 1μF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 17mA @ 120Hz Ripple Current - High Frequency 27.2mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 17mA @ 120Hz Ripple Current - High Frequency 27.2mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	UPS
Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency17mA @ 120HzRipple Current - High Frequency27.2mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	1μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 17mA @ 120Hz Ripple Current - High Frequency 27.2mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 27.2mA @ 10kHz Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 2000 Hrs @ 105°C -40°C ~ 105°C -40°C -40°C ~ 105°C -40°C -40°C ~ 105°C -40°C -40	Voltage - Rated	350V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 17mA @ 120Hz Ripple Current - High Frequency 27.2mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 17mA @ 120Hz Ripple Current - High Frequency 27.2mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 27.2mA @ 10kHz Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency 27.2mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	17mA @ 120Hz
Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	27.2mA @ 10kHz
Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.551" (14.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UPS2V010MPD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UPS2V010MPD Payment Methods



















UPS2V010MPD Shipping Methods













If you have any question about UPS2V010MPD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com