



### **UPT2G390MHD Information**



For Reference Only

Part Number UPT2G390MHD

Manufacturer Nichicon Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 39UF 20% 400V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **UPT2G390MHD Specifications**

Manufacturer Part Number         UPT2G390MHD           Manufacturer         Nichicon           Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can           Series         UPT           Capacitance         39μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -25°C ~ 105°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         320mA @ 120Hz           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.299" (33.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	_	
Category         Capacitors           Package         Radial, Can           Series         UPT           Capacitance         39µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -25°C ~ 105°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         320mA @ 120Hz           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.299" (33.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer Part Number	UPT2G390MHD
Package         Radial, Can           Series         UPT           Capacitance         39μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -25°C ~ 105°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         320mA @ 120Hz           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.299" (33.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer	Nichicon
Package         Radial, Can           Series         UPT           Capacitance         39μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -25°C ~ 105°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         320mA @ 120Hz           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.299" (33.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Category	Capacitors
Series         UPT           Capacitance         39µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -25°C ~ 105°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         320mA @ 120Hz           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.299" (33.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		Aluminum Electrolytic Capacitors
Capacitance         39µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -25°C ~ 105°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         320mA @ 120Hz           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.299" (33.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 400V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C  Operating Temperature -25°C ~ 105°C  Polarization - Applications General Purpose Ripple Current - Low Frequency 320mA @ 120Hz  Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm)  Size / Dimension 0.492" Dia (12.50mm)  Height - Seated (Max) 1.299" (33.00mm)  Surface Mount Land Size - Mounting Type Through Hole  Package / Case Radial, Can	Series	UPT
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  5000 Hrs @ 105°C  Operating Temperature  -25°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  - Impedance  Lead Spacing  0.197" (5.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  Roon Hrs @ 105°C  -25°C ~ 105°C	Capacitance	39μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  5000 Hrs @ 105°C  Operating Temperature  -25°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  320mA @ 120Hz  Ripple Current - High Frequency  Impedance  -  Lead Spacing  0.197" (5.00mm)  Size / Dimension  0.492" Dia (12.50mm)  Height - Seated (Max)  1.299" (33.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Tolerance	±20%
Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency 320mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.299" (33.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Voltage - Rated	400V
Operating Temperature -25°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency 320mA @ 120Hz Ripple Current - High Frequency - Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.299" (33.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization - General Purpose Ripple Current - Low Frequency 320mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.299" (33.00mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  Ripple Current - High Frequency	Operating Temperature	-25°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing O.197" (5.00mm) Size / Dimension O.492" Dia (12.50mm) Height - Seated (Max) 1.299" (33.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Polarization	-
Ripple Current - High Frequency Impedance Lead Spacing O.197" (5.00mm) Size / Dimension O.492" Dia (12.50mm) Height - Seated (Max) I.299" (33.00mm) Surface Mount Land Size  Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.299" (33.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	320mA @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.299" (33.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.492" Dia (12.50mm)  Height - Seated (Max) 1.299" (33.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	1.299" (33.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

### **UPT2G390MHD Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **UPT2G390MHD Payment Methods**



















## **UPT2G390MHD Shipping Methods**













If you have any question about UPT2G390MHD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com