

UPT2P121MHD

Request a Quote

UPT2P121MHD Information

www.nelseng.com	Part Number	UPT2P121MHD
	Manufacturer	Nichicon
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 120UF 20% 220V RADIAL
	Package	Radial, Can
		For the pricing/inventory/lead time, please contact
		us
For Reference Only		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UPT2P121MHD Specifications

Manufacturer Part NumberUPT2P121MHDManufacturer ANichiconCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPTCapacitance120µFTolerance±20%Voltage - Rated20VESR (Equivalent Series Resistance)-Lifetime Ø Temp.5000 Hrs @ 105°COperating Temperature90arApplicationsGeneral PurposeRipple Current - High Frequency784mA @ 10kHzImpedance-Lad Spacing0197" (500mm)Sizer Alomanistion1492" Dia (12.50mm)Bight - Seated (Max)1492" Nig (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / Case-Keptor temp.5000 Hrs (30.00mm)Sizer Alomanistion6019" (50.00mm)Sizer Alomanistic Alo	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPTCapacitance120µFTolerance±20%Voltage - Rated20VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating TemperaturePolarApplicationsGeneral PurposeRipple Current - High Frequency490mA @ 120HzNipple Current - High Frequency0197" (5.00mm)Size / Dimension0.197" (5.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeFinough HolePackage / CaseKadia, Can	Manufacturer Part Number	UPT2P121MHD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPTCapacitance120µFTolerance±20%Voltage - Rated220VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature25°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency784mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Polaring TypeFinough HolePackage / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUPTCapacitance120µFTolerance-20%Voltage - Rated220VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency784mA @ 10kHzImpedance-Lad Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Size / Dimension1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
NewUPTCapacitance120µFTolerance±20%Voltage - Rated20VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency490mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dinension0.492" Dia (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePokang / Case-Ring Polar1.457" (37.00mm)		Aluminum Electrolytic Capacitors
Capacitance120µFTolerance±20%Voltage - Rated220VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency784mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated220VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency490mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Hight - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRatial, Can	Series	UPT
Voltage - Rated220VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency490mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRatial, Can	Capacitance	120µF
LocESR (Equivalent Series Resistance)-ESR (Equivalent Series Resistance)5000 Hrs @ 105°CLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarPolarApplicationsGeneral PurposeRipple Current - Low Frequency490mA @ 120HzMippedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency490mA @ 120HzRipple Current - High Frequency784mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	220V
Operating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency490mA @ 120HzRipple Current - High Frequency784mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency490mA @ 120HzRipple Current - High Frequency784mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency490mA @ 120HzRipple Current - High Frequency784mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can	Operating Temperature	$-25^{\circ}C \sim 105^{\circ}C$
Ripple Current - Low Frequency490mA @ 120HzRipple Current - High Frequency784mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency784mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	490mA @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	784mA @ 10kHz
Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.457" (37.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UPT2P121MHD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UPT2P121MHD Payment Methods



UPT2P121MHD Shipping Methods



If you have any question about UPT2P121MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com