



UPTW6180MPD Information



For Reference Only

Part Number UPTW6180MPD

Manufacturer Nichicon Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 18UF 20% 420V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UPTW6180MPD Specifications

Manufacturer Part NumberUPTW6180MPDManufacturerNichiconCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPTCapacitance18µFTolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°C
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPTCapacitance18μFTolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°C
Package Radial, Can Series UPT Capacitance 18μF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C
Package Radial, Can Series UPT Capacitance 18μF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C
SeriesUPTCapacitance $18\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $420V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $5000 \text{Hrs} \text{@} 105 ^{\circ}\text{C}$
Capacitance $18\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $420V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $5000 \text{Hrs} \text{@} 105 ^{\circ}\text{C}$
Tolerance $\pm 20\%$ Voltage - Rated ± 20 V ESR (Equivalent Series Resistance) - Lifetime @ Temp. $\pm 20\%$
Voltage - Rated 420V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C
ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 105°C
Lifetime @ Temp. 5000 Hrs @ 105°C
-
Operating Temperature $-25^{\circ}\text{C} \sim 105^{\circ}\text{C}$
Polarization -
Applications General Purpose
Ripple Current - Low Frequency 170mA @ 120Hz
Ripple Current - High Frequency 272mA @ 10kHz
Impedance -
Lead Spacing 0.197" (5.00mm)
Size / Dimension 0.394" Dia (10.00mm)
Height - Seated (Max) 1.299" (33.00mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can
Report errors

UPTW6180MPD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UPTW6180MPD Payment Methods



















UPTW6180MPD Shipping Methods













If you have any question about UPTW6180MPD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com