

#### **UPV1A680MFD1TD Information**



For Reference Only

Part Number UPV1A680MFD1TD

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 68UF 20% 10V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **UPV1A680MFD1TD Specifications**

Manufacturer Part Number         UPV 1A680MFD1TD           Manufacturer         Nichicon           Category         Capacitors           Package         Radial, Can           Series         UPV           Capacitance         68μF           Tolerance         ±20%           Voltage - Rated         10V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Lead Spacing         0.079" (2.00mm)           Size / Dimension         0.197" Dia (5.00mm)           Height - Seated (Max)         0.492" (12.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		
Category         Capacitors           Package         Radial, Can           Series         UPV           Capacitance         68µF           Tolerance         ±20%           Voltage - Rated         10V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Oplarization         -           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         1.4 Ohms           Lead Spacing         0.079" (2.00mm)           Size / Dimension         0.197" Dia (5.00mm)           Height - Seated (Max)         0.492" (12.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer Part Number	UPV1A680MFD1TD
Package         Radial, Can           Series         UPV           Capacitance         68µF           Tolerance         ±20%           Voltage - Rated         10V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         1.4 Ohms           Lead Spacing         0.079" (2.00mm)           Size / Dimension         0.197" Dia (5.00mm)           Height - Seated (Max)         0.492" (12.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer	Nichicon
Package         Radial, Can           Series         UPV           Capacitance         68μF           Tolerance         ±20%           Voltage - Rated         10V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         1.4 Ohms           Lead Spacing         0.079" (2.00mm)           Size / Dimension         0.197" Dia (5.00mm)           Height - Seated (Max)         0.492" (12.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Category	Capacitors
Series         UPV           Capacitance         68µF           Tolerance         ±20%           Voltage - Rated         10V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         1.4 Ohms           Lead Spacing         0.079" (2.00mm)           Size / Dimension         0.197" Dia (5.00mm)           Height - Seated (Max)         0.492" (12.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		Aluminum Electrolytic Capacitors
Capacitance         68µF           Tolerance         ±20%           Voltage - Rated         10V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         1.4 Ohms           Lead Spacing         0.079" (2.00mm)           Size / Dimension         0.197" Dia (5.00mm)           Height - Seated (Max)         0.492" (12.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 10V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C  Operating Temperature -55°C ~ 105°C  Polarization - Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance 1.4 Ohms  Lead Spacing 0.079" (2.00mm)  Size / Dimension 0.197" Dia (5.00mm)  Height - Seated (Max) 0.492" (12.50mm)  Surface Mount Land Size - Mounting Type Through Hole  Package / Case Raistance)  10V  - Common 100  - Commo	Series	UPV
Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance1.4 OhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	68μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  5000 Hrs @ 105°C  Operating Temperature  -55°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  -Ripple Current - High Frequency  Impedance  Lead Spacing  0.079" (2.00mm)  Size / Dimension  Height - Seated (Max)  0.492" (12.50mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -55°C ~ 105°C  Polarization  - Applications  General Purpose  Ripple Current - Low Frequency  - Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  5000 Hrs @ 105°C  6000 Hrs @ 105°  60	Voltage - Rated	10V
Operating Temperature  -55°C ~ 105°C  Polarization  -Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  -Impedance  Lead Spacing  O.079" (2.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  -S5°C ~ 105°C  -015°C  -015°  -01	ESR (Equivalent Series Resistance)	-
Polarization - General Purpose  Ripple Current - Low Frequency -  Ripple Current - High Frequency -  Impedance 1.4 Ohms  Lead Spacing 0.079" (2.00mm)  Size / Dimension 0.197" Dia (5.00mm)  Height - Seated (Max) 0.492" (12.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
Applications General Purpose  Ripple Current - Low Frequency -  Ripple Current - High Frequency -  Impedance 1.4 Ohms  Lead Spacing 0.079" (2.00mm)  Size / Dimension 0.197" Dia (5.00mm)  Height - Seated (Max) 0.492" (12.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance 1.4 Ohms Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	-
Ripple Current - High Frequency Impedance 1.4 Ohms Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance1.4 OhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.197" Dia (5.00mm)  Height - Seated (Max) 0.492" (12.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	1.4 Ohms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.079" (2.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.197" Dia (5.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.492" (12.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
•	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### **UPV1A680MFD1TD Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **UPV1A680MFD1TD Payment Methods**





















### **UPV1A680MFD1TD Shipping Methods**













If you have any question about UPV1A680MFD1TD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com