



# **UPV1V470MGD Information**



For Reference Only

Part Number UPV1V470MGD

Manufacturer Nichicon
Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 47UF 20% 35V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **UPV1V470MGD Specifications**

Manufacturer Part Number         UPV1V470MGD           Manufacturer         Nichicon           Category         Capacitors           Package         Aduminum Electrolytic Capacitors           Package         Radial, Can           Series         UPV           Capacitance         47µF           Tolerance         ±20%           Voltage - Rated         35V           ESR (Equivalent Series Resistance)         -           ESR (Equivalent Series Resistance)         5000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           S80 mOhms         -           Lead Spacing         0.098" (2.50mm)           Size / Dimension         0.248" Dia (6.30mm)           Height - Seated (Max)         0.492" (12.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		
Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can           Series         UPV           Capacitance         47μF           Tolerance         ±20%           Voltage - Rated         35 V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         580 mOhms           Lead Spacing         0.098" (2.50mm)           Size / Dimension         0.248" Dia (6.30mm)           Height - Seated (Max)         0.492" (12.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer Part Number	UPV1V470MGD
PackageRadial, CanSeriesUPVCapacitance47µFTolerance±20%Voltage - Rated35 VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance580 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	Nichicon
Package         Radial, Can           Series         UPV           Capacitance         47µF           Tolerance         ±20%           Voltage - Rated         35V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         580 mOhms           Lead Spacing         0.098" (2.50mm)           Size / Dimension         0.248" Dia (6.30mm)           Height - Seated (Max)         0.492" (12.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Category	Capacitors
Series         UPV           Capacitance         47μF           Tolerance         ±20%           Voltage - Rated         35V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         580 mOhms           Lead Spacing         0.098" (2.50mm)           Size / Dimension         0.248" Dia (6.30mm)           Height - Seated (Max)         0.492" (12.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		Aluminum Electrolytic Capacitors
Capacitance         47µF           Tolerance         ±20%           Voltage - Rated         35V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         580 mOhms           Lead Spacing         0.098" (2.50mm)           Size / Dimension         0.248" Dia (6.30mm)           Height - Seated (Max)         0.492" (12.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 35V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C  Operating Temperature -55°C ~ 105°C  Polarization - Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance 580 mOhms  Lead Spacing 0.098" (2.50mm)  Size / Dimension 0.248" Dia (6.30mm)  Height - Seated (Max) 0.492" (12.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Series	UPV
Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance580 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	47μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  5000 Hrs @ 105°C  Operating Temperature  -55°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  -Ripple Current - High Frequency  Impedance  580 mOhms  Lead Spacing  0.098" (2.50mm)  Size / Dimension  0.248" Dia (6.30mm)  Height - Seated (Max)  0.492" (12.50mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Tolerance	±20%
Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance 580 mOhms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Voltage - Rated	35V
Operating Temperature -55°C ~ 105°C  Polarization -  Applications General Purpose  Ripple Current - Low Frequency -  Ripple Current - High Frequency -  Impedance 580 mOhms  Lead Spacing 0.098" (2.50mm)  Size / Dimension 0.248" Dia (6.30mm)  Height - Seated (Max) 0.492" (12.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization - General Purpose  Ripple Current - Low Frequency - Frequency - Impedance 580 mOhms  Lead Spacing 0.098" (2.50mm)  Size / Dimension 0.248" Dia (6.30mm)  Height - Seated (Max) 0.492" (12.50mm)  Surface Mount Land Size - Ihrough Hole  Package / Case Radial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
Applications  Ripple Current - Low Frequency	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance 580 mOhms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	-
Ripple Current - High Frequency Impedance 580 mOhms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance580 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing 0.098" (2.50mm)  Size / Dimension 0.248" Dia (6.30mm)  Height - Seated (Max) 0.492" (12.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.248" Dia (6.30mm)  Height - Seated (Max) 0.492" (12.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	580 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.248" Dia (6.30mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.492" (12.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### **UPV1V470MGD Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **UPV1V470MGD Payment Methods**



















### **UPV1V470MGD Shipping Methods**













If you have any question about UPV1V470MGD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com