



UPW1E270MDH Information



For Reference Only

Part Number UPW1E270MDH

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 27UF 20% 25V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UPW1E270MDH Specifications

Manufacturer Part Number UPW 1E270MDH Manufacturer Nichicon Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series UPW Capacitance 27μF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 36mA @ 120Hz Ripple Current - High Frequency - Impedance 1.3 Ohms Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.433" (11.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		
Category Capacitors Package Radial, Can Series UPW Capacitance 27µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 36mA @ 120Hz Ripple Current - High Frequency - Impedance 1.3 Ohms Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.433" (11.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	UPW1E270MDH
Package Radial, Can Series UPW Capacitance 27μF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 36mA @ 120Hz Ripple Current - High Frequency - Impedance 1.3 Ohms Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.433" (11.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	Nichicon
Package Radial, Can Series UPW Capacitance 27μF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 36mA @ 120Hz Ripple Current - High Frequency - Impedance 1.3 Ohms Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.433" (11.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series UPW Capacitance 27µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 36mA @ 120Hz Ripple Current - High Frequency - Impedance 1.3 Ohms Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.433" (11.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 27µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 36mA @ 120Hz Ripple Current - High Frequency - Impedance 1.3 Ohms Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.433" (11.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 36mA @ 120Hz Ripple Current - High Frequency - Impedance 1.3 Ohms Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.433" (11.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	UPW
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.3 Ohms Lead Spacing 0.059" (1.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Polor Too Office (Account) Package / Case Polor (105°C General Purpose General Purpose 36mA @ 120Hz 1.3 Ohms 0.157" Dia (4.00mm) 0.157" Dia (4.00mm) Through Hole Radial, Can	Capacitance	27μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.3 Ohms Lead Spacing 0.059" (1.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Polar 2000 Hrs @ 105°C 2000	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance 1.3 Ohms Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 2000 Hrs @ 105°C -55°C ~ 105°C Folar -55°C ~ 105°C -500 An	Voltage - Rated	25V
Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance 1.3 Ohms Lead Spacing 0.059" (1.50mm) Size / Dimension Height - Seated (Max) Outling Type Mounting Type Through Hole Package / Case Raplace -55°C ~ 105°C Roperal Purpose General Purpose 36mA @ 120Hz - 0.059" (1.50mm) - 1.3 Ohms 0.157" Dia (4.00mm) -1.50mm) -1.50mm) -1.50mm -1.50	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 36mA @ 120Hz Ripple Current - High Frequency - Impedance 1.3 Ohms Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.433" (11.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 1.3 Ohms Lead Spacing 0.059" (1.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Ingedance Lead Spacing Current - Mount Ingedance Lead Spacing Current - High Frequency 1.3 Ohms Current - High Frequency Current - High Frequency 1.3 Ohms Current - High Frequency Current - High F	Polarization	Polar
Ripple Current - High Frequency Impedance Ingedance I.3 Ohms Lead Spacing O.059" (1.50mm) Size / Dimension O.157" Dia (4.00mm) Height - Seated (Max) O.433" (11.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance1.3 OhmsLead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	36mA @ 120Hz
Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.433" (11.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.433" (11.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	1.3 Ohms
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.059" (1.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.157" Dia (4.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.433" (11.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UPW1E270MDH Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UPW1E270MDH Payment Methods





















UPW1E270MDH Shipping Methods













If you have any question about UPW1E270MDH, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com