

UPW1E330MDD

UPW1E330MDD Information



Part Number	UPW1E330MDD	
Manufacturer	Nichicon	
Category	Capacitors Aluminum Electrolytic Capacitors	
Description	CAP ALUM 33UF 20% 25V RADIAL	
Package	Radial, Can	
	For the pricing/inventory/lead time, please contact	
us		
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UPW1E330MDD Specifications

Manufacturer Part NumberUPW 1E330MDDManufacturerNichiconCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPWCapacitance3JgFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-0000 Hrs @105°COperating Temp.0000 Hrs @105°COpartardon55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High FrequencyManufa (200mm)Lied Spacing0079° (2.00mm)Size / Dimension0.197° Dia (5.00mm)Size / Dimension0.197° Dia (5.00mm)Martafa Company-Manufa Type-Surface Mount Land Size-Mounting TypeFinough HeleMacha Case-Mounting TypeKadia, CanManume Manuel Case-Mounting Type-Manume Manuel Case-Manume Manuel Case-Manuel Case-Manuel Case-Manuel Case-Manuel Case-Manuel Case-Manuel Case-Manuel Case-Manuel CaseManu	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPWCapacitance33µFTolerance±20%Voltage - RatedSVESR (Equivalent Series Resistance)-Lifetime Temp.2000 Hrs @ 105°COperating Temperature90arOperating TemperatureSvApplicationsGeneral PurposeRippe Current - High Frequency810m A@ 100kHzImpedance600 mOhmsLiad Spacing0.197° 10.00mn)Size / Dimension0.197° Dia (5.00mn)Hight - Seated (Max)0.433° (11.00mm)Surface Mount Land Size-Anunting TypeFinough HolePackage / CaseKadia, Can	Manufacturer Part Number	UPW1E330MDD
IdentifyAluminu Electrolytic CapacitorsPackageRadial, CanSeriesUPWCapacitance33µFTolerance-20%Voltage - RatedSVESR (Equivalent Series Resistance)-Derating Temper2000 Hrs @ 105°COperating TemperatureSolor SCPolarizationFolaranceApplicationsGeneral PurposeRipple Current - Low FrequencyS4mA @ 100kHzRipple Current - High Frequency000 mOhmsLied Spacing0.79° (2.00mm)Siz / Dimension0.197° Dia (5.00mm)Siz / Dimension0.43° (11.00mm)Surface MoutLand Size-Mouting TypeFolareatPackage / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUPWCapacitance33µFTolerance-20%Voltage - RatedSVESR (Equivalent Series Resistance)-Jeritem @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplicationsS4mA @ 120HzRipple Current - High Frequency600 mOhmsLied Spacing0.079" (2.00mm)Siz / Dimension0.197" Dia (5.00mm)Siz / Dimension0.433" (11.00mm)Sirface Mount Land Size-Mounting TypeFinough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesUPWCapacitance33μFTolerance±20%Voltage - Rated55VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency54mA @ 120HzImpedance600 mOhmsLiad Spacing0.197° Dia (5.00mm)Size / Dimension0.197° Dia (5.00mm)Surface Mount Land Size-Mounting TypeThrough HolePokang CraseMang Hole		Aluminum Electrolytic Capacitors
Capacitance33µFTolerance±20%Voltage Rated55VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency180mA @ 100kHzImpedance600 mOhmsLiad Spacing0.197° (2.00mm)Size / Dimension0.433° (11.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarPolarApplicationsGeneral PurposeRipple Current - High Frequency54mA @ 120HzImpedance600 mOhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Staff - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Series	UPW
Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency54mA @ 120HzBipple Current - High Frequency600 mOhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	33µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency54mA @ 120HzImpedance600 mOhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)-Nurface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency54mA @ 120HzBippe Current - High Frequency180mA @ 100kHzImpedance600 mOhmsLead Spacing0.079" (2.00mm)Size / Dimension0.433" (11.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	25V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency54mA @ 120HzBipple Current - High Frequency180mA @ 100kHzImpedance600 mOhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, CanRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency54mA @ 120HzRipple Current - High Frequency180mA @ 100kHzImpedance600 mOhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency54mA @ 120HzRipple Current - High Frequency180mA @ 100kHzImpedance600 mOhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55° C ~ 105° C
Ripple Current - Low Frequency54mA @ 120HzRipple Current - High Frequency180mA @ 100kHzImpedance600 mOhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In or of a part of a	Applications	General Purpose
Impedance600 mOhmsLead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	54mA @ 120Hz
Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.433" (11.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	180mA @ 100kHz
Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	600 mOhms
Height - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.079" (2.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.197" Dia (5.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.433" (11.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
	Package / Case	Radial, Can
Report errors?		Report errors?

UPW1E330MDD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UPW1E330MDD Payment Methods



UPW1E330MDD Shipping Methods



If you have any question about UPW1E330MDD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com