

# UPW1V470MED

## **UPW1V470MED Information**



For Reference Only

Part Number	UPW1V470MED	
Manufacturer	Nichicon	
Category	Capacitors Aluminum Electrolytic Capacitors	
Description	CAP ALUM 47UF 20% 35V RADIAL	
Package	Radial, Can	
	For the pricing/inventory/lead time, please contact	
us		
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **UPW1V470MED Specifications**

ManufacturerNichiconCapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPWCapacitance47µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency90mA @ 100kHzImpedance250 mOhmsLied Spacing0.098" (2.50mm)Size / Dimension0.443" (11.00mm)Height - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-Package / CaseKadial, Can	_	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageRadial, CanSeriesUPWCapacitance47µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency87mA @ 120HzImpedance250 mOhmsLied Spacing0.098° (2.50mm)Siz / Dimension0.433° (11.00mm)Height - Seated (Max)0.433° (11.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer Part Number	UPW1V470MED
Aluminum Electrolytic CapacitorsPackageRadial, CanStriesUPWCapacitance47µFTolerance20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplicationsS7MA @ 100HzRipple Current - High Frequency90mA @ 100HzInpedance250 mOhmsLad Spacing0.098" (2.50mm)Siz / Dimension0.433" (11.00mm)Height - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-Package / CaseKadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUPWCapacitance47µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolariPolarApplicationsGeneral PurposeRipple Current - High Frequency250 mOhmsImpedance250 mOhmsLad Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Sirface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesUPWCapacitance47μFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency290mA @ 100kHzImpedance250 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.433" (11.00mm)Height - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-Package / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance47µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency290mA @ 100kHzImpedance250 mOhmsLead Spacing0.098° (2.50mm)Size / Dimension0.248° Dia (6.30mm)Height - Seated (Max)-Surface Mount Land Size-Pokage / CaseRidal, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency87mA @ 120HzRipple Current - High Frequency290mA @ 100kHzImpedance250 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.433" (11.00mm)Height - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Series	UPW
Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency87mA @ 120HzBipple Current - High Frequency290mA @ 100kHzImpedance250 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.433" (11.00mm)Height - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Capacitance	47µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency87mA @ 120HzBipple Current - High Frequency290mA @ 100kHzImpedance250 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency87mA @ 120HzBripple Current - High Frequency290mA @ 100kHzImpedance250 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	35V
Operating Temperature -55°C ~ 105°C   Polarization Polar   Applications General Purpose   Ripple Current - Low Frequency 87mA @ 120Hz   Ripple Current - High Frequency 290mA @ 100kHz   Impedance 250 mOhms   Lead Spacing 0.098" (2.50mm)   Size / Dimension 0.248" Dia (6.30mm)   Height - Seated (Max) 0.433" (11.00mm)   Surface Mount Land Size -   Mounting Type Through Hole   Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency87mA @ 120HzRipple Current - High Frequency290mA @ 100kHzImpedance250 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency87mA @ 120HzRipple Current - High Frequency290mA @ 100kHzImpedance250 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency87mA @ 120HzRipple Current - High Frequency290mA @ 100kHzImpedance250 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
InInRipple Current - High Frequency290mA @ 100kHzImpedance250 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance250 mOhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	87mA @ 120Hz
IILead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	290mA @ 100kHz
Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	250 mOhms
Height - Seated (Max)0.433" (11.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.248" Dia (6.30mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.433" (11.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### **UPW1V470MED Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### **UPW1V470MED Payment Methods**



# **UPW1V470MED Shipping Methods**



If you have any question about UPW1V470MED, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com