

UPW2C470MHD

UPW2C470MHD Information



Part Number	UPW2C470MHD	
Manufacturer	Nichicon	
Category	Capacitors Aluminum Electrolytic Capacitors	
Description	CAP ALUM 47UF 20% 160V RADIAL	
Package	Radial, Can	
	For the pricing/inventory/lead time, please contact us	
	Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UPW2C470MHD Specifications

ManufacturerNichiconCagacitorsAluminum Electrolytic CagacitorsPackageRadial, CanPackageRadial, CanSeriesUPWCapacitance47µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature90arApplicationsGeneral PurposeRipple Current - Low Frequency32m A @ 10kHzImpedance-Lied Spacing0.197" (5.00mm)Size / Dimension0.944" (25.00mm)Height - Seated (Max)0.944" (25.00mm)Surface Mount Land Size-Mounting TypeThrough Hole		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageRadial, CanSeriesUPWCapacitance47µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency352mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.944" (25.00mm)Height - Seated (Max)0.944" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer Part Number	UPW2C470MHD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPWCapacitance47µFTolerance±20%Voltage - Rated60VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency322mA @ 120HzRipple Current - High Frequency522mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.984" (25.00mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Package / CaseKadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUPWCapacitance47µFTolerance±20%Voltage - Rated60VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRiple Current - Low Frequency3220mA @ 120HzRiple Current - High Frequency522mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can	Category	Capacitors
SeriesUPWCapacitance47μFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency320mA @ 120HzInpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance47µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency220mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency220mA @ 120HzBipple Current - High Frequency352mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.984" (25.00mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	UPW
Voltage - RatedInformationVoltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency220mA @ 120HzRipple Current - High Frequency352mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Pockage / CaseRadial, Can	Capacitance	47µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency220mA @ 120HzBipple Current - High Frequency352mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Pounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency220mA @ 120HzBipple Current - High Frequency352mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.984" (25.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	160V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency220mA @ 120HzBipple Current - High Frequency352mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency220mA @ 120HzRipple Current - High Frequency352mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	7000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency220mA @ 120HzRipple Current - High Frequency352mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 105^{\circ}\mathrm{C}$
Ripple Current - Low Frequency220mA @ 120HzRipple Current - High Frequency352mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency352mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	220mA @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	352mA @ 10kHz
Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.984" (25.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UPW2C470MHD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UPW2C470MHD Payment Methods



UPW2C470MHD Shipping Methods



If you have any question about UPW2C470MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com