

UPW2D330MHD

UPW2D330MHD Information



Part Number	UPW2D330MHD	
Manufacturer	Nichicon	
Category	Capacitors Aluminum Electrolytic Capacitors	
Description	CAP ALUM 33UF 20% 200V RADIAL	
Package	Radial, Can	
	For the pricing/inventory/lead time, please contact	
us		
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UPW2D330MHD Specifications

ManufacturerNichiconCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPWCapacitance3JFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature90arApplicationsGeneral PurposeRipple Current - High Frequency90mA @ 120HzRipple Current - High Frequency304mA @ 10kHzImpedance-Lead Spacing0.197" (5.0mm)Siz / Dimension0.944" (25.0mm)Height - Seated (Max)9.944" (25.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	_	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageRadial, CanSeriesUPWCapacitance33µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency304mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.949" Dia (12.50mm)Height - Seated (Max)0.944" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer Part Number	UPW2D330MHD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUPWCapacitance33µFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency190mA @ 120HzRipple Current - High Frequency304mA @ 10kHzImpedance-Lead Spacing0.197° (5.00mm)Size / Dimension0.984" (25.00mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUPWCapacitance33µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRiple Current - Low Frequency190mA @ 120HzRiple Current - High Frequency304mA @ 10kHzImpedance-Lead Spacing0.197° (5.00mm)Size / Dimension0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesUPWCapacitance33µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency304mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.944" (25.00mm)Bight - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance33µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency304mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Polaring TypeThrough HolePackage / CaseRadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency190mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.984" (25.00mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	UPW
Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency190mA @ 120HzBipple Current - High Frequency304mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.984" (25.00mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Pockage / CaseRadial, Can	Capacitance	33µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency190mA @ 120HzBipple Current - High Frequency304mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Pounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency190mA @ 120HzBipple Current - High Frequency304mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.984" (25.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	200V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 190mA @ 120Hz Ripple Current - High Frequency 304mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.984" (25.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency190mA @ 120HzRipple Current - High Frequency304mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	7000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency190mA @ 120HzRipple Current - High Frequency304mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 105^{\circ}\mathrm{C}$
Ripple Current - Low Frequency190mA @ 120HzRipple Current - High Frequency304mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency304mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	190mA @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	304mA @ 10kHz
Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.984" (25.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UPW2D330MHD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UPW2D330MHD Payment Methods



UPW2D330MHD Shipping Methods



If you have any question about UPW2D330MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com