



### **UPX1C222MHD Information**



For Reference Only

Part Number UPX1C222MHD

Manufacturer Nichicon
Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 2200UF 20% 16V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **UPX1C222MHD Specifications**

Manufacturer Part Number         UPX1C222MHD           Manufacturer         Nichicon           Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can           Series         UPX           Capacitance         2200µF           Tolerance         ±20%           Voltage - Rated         16V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         20000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         1.512A @ 120Hz           Ripple Current - High Frequency         2.016A @ 100kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.709" Dia (18.00mm)           Height - Seated (Max)         1.457" (37.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		
Category         Capacitors           Package         Radial, Can           Series         UPX           Capacitance         2200µF           Tolerance         ±20%           Voltage - Rated         16V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         20000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         1.512A @ 120Hz           Ripple Current - High Frequency         2.016A @ 100kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.709" Dia (18.00mm)           Height - Seated (Max)         1.457" (37.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer Part Number	UPX1C222MHD
Package         Radial, Can           Series         UPX           Capacitance         2200μF           Tolerance         ±20%           Voltage - Rated         16V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         20000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         1.512A @ 120Hz           Ripple Current - High Frequency         2.016A @ 100kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.709" Dia (18.00mm)           Height - Seated (Max)         1.457" (37.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer	Nichicon
Package         Radial, Can           Series         UPX           Capacitance         2200µF           Tolerance         ±20%           Voltage - Rated         16V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         20000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         1.512A @ 120Hz           Ripple Current - High Frequency         2.016A @ 100kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.709" Dia (18.00mm)           Height - Seated (Max)         1.457" (37.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Category	Capacitors
Series         UPX           Capacitance         2200μF           Tolerance         ±20%           Voltage - Rated         16V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         20000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         1.512A @ 120Hz           Ripple Current - High Frequency         2.016A @ 100kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.709" Dia (18.00mm)           Height - Seated (Max)         1.457" (37.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		Aluminum Electrolytic Capacitors
Capacitance         2200μF           Tolerance         ±20%           Voltage - Rated         16V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         20000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         1.512A @ 120Hz           Ripple Current - High Frequency         2.016A @ 100kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.709" Dia (18.00mm)           Height - Seated (Max)         1.457" (37.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 16V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 20000 Hrs @ 105°C  Operating Temperature -55°C ~ 105°C  Polarization - Applications General Purpose Ripple Current - Low Frequency 1.512A @ 120Hz Ripple Current - High Frequency 2.016A @ 100kHz  Impedance - Lead Spacing 0.295" (7.50mm)  Size / Dimension 0.709" Dia (18.00mm)  Height - Seated (Max) 1.457" (37.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Series	UPX
Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.20000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency1.512A @ 120HzRipple Current - High Frequency2.016A @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	2200μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  20000 Hrs @ 105°C  Operating Temperature  -55°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  1.512A @ 120Hz  Ripple Current - High Frequency  2.016A @ 100kHz  Impedance  -  Lead Spacing  0.295" (7.50mm)  Size / Dimension  0.709" Dia (18.00mm)  Height - Seated (Max)  1.457" (37.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -55°C ~ 105°C  Polarization  - Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  2.016A @ 120Hz  Impedance  Lead Spacing  0.295" (7.50mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  20000 Hrs @ 105°C  -55°C ~ 105°C  -51°C  -51	Voltage - Rated	16V
Operating Temperature -55°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency 1.512A @ 120Hz Ripple Current - High Frequency 2.016A @ 100kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization - General Purpose Ripple Current - Low Frequency 1.512A @ 120Hz Ripple Current - High Frequency 2.016A @ 100kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can	Lifetime @ Temp.	20000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 1.512A @ 120Hz Ripple Current - High Frequency 2.016A @ 100kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  2.016A @ 100kHz  Impedance  - Lead Spacing  0.295" (7.50mm)  Size / Dimension  0.709" Dia (18.00mm)  Height - Seated (Max)  1.457" (37.00mm)  Surface Mount Land Size  - Mounting Type  Through Hole  Package / Case  Radial, Can	Polarization	-
Ripple Current - High Frequency  2.016A @ 100kHz  Impedance - Lead Spacing 0.295" (7.50mm)  Size / Dimension 0.709" Dia (18.00mm)  Height - Seated (Max) 1.457" (37.00mm)  Surface Mount Land Size - Mounting Type Through Hole  Package / Case Radial, Can	Applications	General Purpose
Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	1.512A @ 120Hz
Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	2.016A @ 100kHz
Size / Dimension 0.709" Dia (18.00mm)  Height - Seated (Max) 1.457" (37.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.709" Dia (18.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	1.457" (37.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

### **UPX1C222MHD Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **UPX1C222MHD Payment Methods**



















### **UPX1C222MHD Shipping Methods**













If you have any question about UPX1C222MHD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com