

# URS1A330MDD

#### **URS1A330MDD** Information

www.helsener.com	Part Number	URS1A330MDD	
	Manufacturer	Nichicon	- Instan
	Category	Capacitors Aluminum Electrolytic Capacitors	- <u>687</u> 77
	Description	CAP ALUM 33UF 20% 10V RADIAL	- : 35 - <b>: 3</b> 5
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact us	- E1936220
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **URS1A330MDD Specifications**

ManufacturerNichiconCapacitorsCapacitorsAtuminum Electrolytic CapacitorsPackageRadial, CanSeriesURSCapacitance33µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplications50mA @ 10kHzRipple Current - High Frequency150mA @ 10kHzImpedance-Lide Spacing0.079° (2.00mm)Siz / Dimension0.197° Dia (5.00mm)Height - Seated (Max)0.413° (10.50mm)Surface Mount Land Size-Mounting TypeThrough Hole		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageRadial, CanSeriesURSCapacitance33µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency150mA @ 10kHzRipple Current - High Frequency150mA @ 10kHzImpedance-Lief Spacing0.079° (2.00mm)Size / Dimension0.197° Dia (5.00mm)Height - Seated (Max)0.413° (10.50mm)Surface Mount Land Size-Package / CaseRation, CanPackage / CaseRation, Can	Manufacturer Part Number	URS1A330MDD
Aluminum Electrolytic CapacitorsPackageRadial, CanPackageURSCapacitance33µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ remp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency55mA @ 120HzRipple Current - High Frequency150mA @ 10kHzBingedance-Lad Spacing0.079° (2.00mm)Size / Dimension0.197° Dia (5.00mm)Size / Dimension0.413° (10.50mm)Surface Mount Land Size-Package / CaseKaila, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesURSCapacitance33µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency75mA @ 120HzRipple Current - High Frequency150mA @ 10kHzBippe Current - High Frequency0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Size / Dimension0.413" (10.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Category	Capacitors
SeriesURSCapacitance33µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency75mA @ 120HzRipple Current - High Frequency150mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can		Aluminum Electrolytic Capacitors
Capacitance33µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency150mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Package / CaseKadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency75mA @ 120HzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Package / CaseRatio AgeRatio Age-Reing Package / Case-Rota Ratio Age-Ring Ratio Age	Series	URS
Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency75mA @ 120HzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.413" (10.50mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Capacitance	33µF
Constraint-ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency75mA @ 120HzBipple Current - High Frequency150mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeApple Current - Low Frequency75mA @ 120HzBripple Current - High Frequency150mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can	Voltage - Rated	10V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency75mA @ 120HzRipple Current - High Frequency150mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Package / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency75mA @ 120HzBipple Current - High Frequency150mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency75mA @ 120HzRipple Current - High Frequency150mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency75mA @ 120HzRipple Current - High Frequency150mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	75mA @ 120Hz
Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	150mA @ 10kHz
Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.079" (2.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.197" Dia (5.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.413" (10.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### **URS1A330MDD** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE ELARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **URS1A330MDD** Payment Methods



### **URS1A330MDD** Shipping Methods



If you have any question about URS1A330MDD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com