

# URS1H3R3MDD

## **URS1H3R3MDD** Information

www.helsener.com	Part Number Manufacturer Category Description Package	URS1H3R3MDD Nichicon Capacitors Aluminum Electrolytic Capacitors CAP ALUM 3.3UF 20% 50V RADIAL Radial, Can	
	Package	For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **URS1H3R3MDD** Specifications

ManufacturerNichiconCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanStriesURSCapacitance3.3µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Operating Temperature2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Hounting TypeFincuge HolePackage / CaseKadial, Can	•	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesURSCapacitance3.3µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime Temp.2000 Hrs @ S°COperating Temperature90arApplicationsGeneral PurposeRipple Current - High Frequency55mA @ 120HzNipple Current - High Frequency-Lied Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseKail, Can	Manufacturer Part Number	URS1H3R3MDD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesURSCapacitance3.3µFTolerance±20%Voltage - RatedSoVESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lided Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Size / Dimension0.413" (10.50mm)Height - Seated (Max)-Mounting TypeFincuga HolePackage / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesURSCapacitance3.3µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRiple Current - Low Frequency-Impedance-Lided Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Size / Dimension0.413" (10.50mm)Surface Mount Land Size-Mounting TypeFanceancePackage / CaseRadial, Can	Category	Capacitors
NewURSCapacitance3.3µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency35mA @ 120HzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)-Mounting Type-Potarging Type-Straface Mount Land Size-Potarging Type-Straface Mount Land Size-Potarging Type-Potarging Type-Straface Mount Land Size-Potarging Type-Potarging Type- <td></td> <td>Aluminum Electrolytic Capacitors</td>		Aluminum Electrolytic Capacitors
Capacitance3.3µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance-Lead Spacing0.079° (2.00mm)Size / Dimension0.413° (10.50mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency35mA @ 120HzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Hight - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Series	URS
Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency35mA @ 120HzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRatial, Can	Capacitance	3.3µF
ConstructESR (Equivalent Series Resistance)-ESR (Equivalent Series Resistance)2000 Hrs @ 85°CLifetime @ TempOperating Temperature-PolarPolarApplicationsGeneral PurposeRipple Current - Low Frequency35mA @ 120HzNippedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency35mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeRadial, Can	Voltage - Rated	50V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency35mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency35mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency35mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 85^{\circ}\mathrm{C}$
Ripple Current - Low Frequency35mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	35mA @ 120Hz
Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.079" (2.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.197" Dia (5.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.413" (10.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### **URS1H3R3MDD** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### **URS1H3R3MDD** Payment Methods



## **URS1H3R3MDD** Shipping Methods



If you have any question about URS1H3R3MDD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com