

URS1HR47MDD

URS1HR47MDD Information

www.heisen	Part Numl Manufactu Category Descriptio Package	 nrer Nichicon Capacitors Aluminum Electrolytic Capacitors n CAP ALUM 0.47UF 20% 50V RADIAL Radial, Can 	
		For the pricing/inventory/lead time, please contact us	E 169754
For Ref	erence Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



URS1HR47MDD Specifications

ManufacturerNichiconCatagoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesURSCapacitance0.47µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature901arApplicationsGeneral PurposeRipple Current - High Frequency5mA @ 120HzRipple Current - High Frequency0.079° (2.00mm)Size / Dimension0.197° Dia (5.00mm)Height - Seated (Max)0.413° (10.50mm)Surface Mount Land Size-Package / CaseKaila, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesURSCapacitance0.47µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency5mA @ 120HzRipple Current - High Frequency10mA @ 10kHzImpedance-Lief Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer Part Number	URS1HR47MDD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesURSCapacitance0.47μFTolerance±20%Voltage - RatedSoVESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency5mA @ 120HzRipple Current - High Frequency10mA @ 10kHzImpedance-Lead Spacing0.079° (2.00mm)Size / Dimension0.197° Dia (5.00mm)Strace Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesURSCapacitance0.47µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency5mA @ 120HzRiple Current - High Frequency10mA @ 10kHzImpedance-Lead Spacing0.197° Dia (5.00mm)Size / Dimension0.413° (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesURSCapacitance0.47µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5mA @ 120HzRipple Current - High Frequency10mA @ 10kHzImpedance-Lead Spacing0.197" Dia (5.00mm)Size / Dimension0.413" (10.50mm)Height - Seated (Max)-Mounting TypeThrough HolePackage / CaseRadial, Can		Aluminum Electrolytic Capacitors
Capacitance0.47µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5mA @ 100HzInpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Pokage / CaseKadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5mA @ 120HzImpedance-Lead Spacing0.079° (2.00mm)Size / Dimension0.197° Dia (5.00mm)Height - Seated (Max)0.413° (10.50mm)Surface Mount Land Size-Package / CaseRatial, Can	Series	URS
Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5mA @ 120HzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.413" (10.50mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Capacitance	0.47µF
ComponentESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5mA @ 120HzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5mA @ 120HzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	50V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5mA @ 120HzRipple Current - High Frequency10mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Package / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency5mA @ 120HzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency5mA @ 120HzRipple Current - High Frequency10mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency5mA @ 120HzRipple Current - High Frequency10mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
InInRipple Current - High Frequency10mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	5mA @ 120Hz
Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	10mA @ 10kHz
Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.079" (2.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.197" Dia (5.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.413" (10.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

URS1HR47MDD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

URS1HR47MDD Payment Methods



URS1HR47MDD Shipping Methods



If you have any question about URS1HR47MDD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com