

URZ1A222MHD

URZ1A222MHD Information





Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



URZ1A222MHD Specifications

ManufacturerNichiconCapacitorsCapacitorsAtuminum Electrolytic CapacitorsPackageRadial, CanSeriesURZCapacitance200µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency690mA @ 120HzRipple Current - High Frequency93.5mA @ 10kHzImpedance-Lied Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	_	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageRadial, CanSeriesURZCapacitance200µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency690mA @ 120HzRipple Current - High Frequency793.5mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Package / CaseRatio, Can	Manufacturer Part Number	URZ1A222MHD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesURZCapacitance2200µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency690mA @ 120HzRipple Current - High Frequency793.5mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesURZCapacitance2200µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency690mA @ 120HzRipple Current - High Frequency793.5mA @ 10kHzImpedance-Lad Spacing0.197" (5.00mm)Size / Dimension0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SerieURZCapacitance220µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency690mA @ 120HzRipple Current - High Frequency0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Package / CaseRatial, Can		Aluminum Electrolytic Capacitors
Capacitance2200μFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency690mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Package / CaseKadial, Can	Package	Radial, Can
Tolerance±0%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency690mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Package / CaseRatial, Can	Series	URZ
Voltage - RatedI0VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency690mA @ 120HzBipple Current - High Frequency793.5mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Package / CaseRatial, Can	Capacitance	2200µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency690mA @ 120HzBipple Current - High Frequency793.5mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency690mA @ 120HzRipple Current - High Frequency793.5mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	10V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency690mA @ 120HzRipple Current - High Frequency793.5mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency690mA @ 120HzRipple Current - High Frequency793.5mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency690mA @ 120HzRipple Current - High Frequency793.5mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
AFRipple Current - Low Frequency690mA @ 120HzRipple Current - High Frequency793.5mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	690mA @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	793.5mA @ 10kHz
Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.650" (16.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

URZ1A222MHD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

URZ1A222MHD Payment Methods



URZ1A222MHD Shipping Methods



If you have any question about URZ1A222MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com