



URZ1E332MHD Information



For Reference Only

Part Number URZ1E332MHD

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 3300UF 20% 25V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









URZ1E332MHD Specifications

Manufacturer Part Number URZ IE332MHD Manufacturer Nichicon Category Capacitors Package Radial, Can Series URZ Capacitance 3300µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization General Purpose Ripple Current - Low Frequency 1,22A @ 120Hz Ripple Current - High Frequency 1,403A @ 10kHz Impedance - Lead Spacing 0,295" (7.50mm) Size / Dimension 0,709" Dia (18.00mm) Height - Seated (Max) 0,846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series URZ Capacitance 3300µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.22A @ 120Hz Ripple Current - High Frequency 1.403A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	URZ1E332MHD
PackageRadial, CanSeriesURZCapacitance3300μFTolerance±20%Voltage - Rated25 VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.22A @ 120HzRipple Current - High Frequency1.403A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	Nichicon
Package Radial, Can Series URZ Capacitance 3300µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.22A @ 120Hz Ripple Current - High Frequency 1.403A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series URZ Capacitance 3300µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.22A @ 120Hz Ripple Current - High Frequency 1.403A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 3300μF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.22A @ 120Hz Ripple Current - High Frequency 1.403A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.22A @ 120Hz Ripple Current - High Frequency 1.403A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	URZ
Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.22A @ 120HzRipple Current - High Frequency1.403A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	3300μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 1.22A @ 120Hz Ripple Current - High Frequency 1.403A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 1.22A @ 120Hz Ripple Current - High Frequency 1.403A @ 10kHz Impedance Lead Spacing 0.295" (7.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 1000 Hrs @ 105°C -55°C ~ 105°C Roneral Purpose 1.22A @ 120Hz 1.403A @ 10kHz - 1.403A @ 10	Voltage - Rated	25V
Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.22A @ 120Hz Ripple Current - High Frequency 1.403A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.22A @ 120Hz Ripple Current - High Frequency 1.403A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	1000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 1.22A @ 120Hz Ripple Current - High Frequency 1.403A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency 1.403A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	1.22A @ 120Hz
Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	1.403A @ 10kHz
Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.709" Dia (18.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.846" (21.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

URZ1E332MHD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

URZ1E332MHD Payment Methods



















URZ1E332MHD Shipping Methods













If you have any question about URZ1E332MHD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com