

URZ1V4R7MDD

URZ1V4R7MDD Information

www.helsener.com	Part Number Manufacturer Category Description Package	URZ1V4R7MDD Nichicon Capacitors Aluminum Electrolytic Capacitors CAP ALUM 4.7UF 20% 35V RADIAL Radial, Can For the pricing/inventory/lead time, please contact	
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



URZ1V4R7MDD Specifications

ManufacturerNichiconCapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesURZCapacitance4.7µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency50mA @ 10kHzImpedance-Lied Spacing0.079° (2.00mm)Size / Dimension0.197° Dia (5.00mm)Height - Seated (Max)0.413° (10.50mm)Surface Mount Land Size-Package / CaseKadial, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesURZCapacitance4.7µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency50mA @ 10kHzImpedance-Lied Spacing0.079° (2.00mm)Siz / Dimension0.197° Dia (5.00mm)Height - Seated (Max)0.413° (10.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer Part Number	URZ1V4R7MDD
Aluminum Electrolytic CapacitorsPackageRadial, CanPackageRadial, CanStriesURZCapacitance4.7µFTolerance±20%Voltage - Rated55VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature55°C ~ 105°C ~ 105°CPolarizationCeneral PurposeApplicationsSonA @ 10HzRipple Current - High Frequency50mA @ 10HzRipple Current - High Frequency0.079° (2.00mm)Siz / Dimension0.197° Dia (5.00mm)Siz / Dimension0.413° (10.50mm)Strafae Mount Land Size-Package / CaseKadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesURZCapacitance4.7µFTolerance±20%Voltage - Rated55VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApple Current - Low Frequency55°M @ 104HZRipple Current - High Frequency50mA @ 104HZImpedance-Lad Spacing0.079° (2.00mm)Siz / Dimension0.197° Dia (5.00mm)Sirface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can	Category	Capacitors
SeriesURZCapacitance4.7μFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency50mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Bieght - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Package / CaseRadial, Can		Aluminum Electrolytic Capacitors
Capacitance4.7µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency50mA @ 10kHzImpedance-Lead Spacing0.197" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)-Surface Mount Land Size-Polaring TypeThrough HolePackage / CaseKalial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency25mA @ 120HzBipple Current - High Frequency0079° (2.00mm)Size / Dimension0.197° Dia (5.00mm)Height - Seated (Max)0.413° (10.50mm)Surface Mount Land Size-Package / CaseRatial, Can	Series	URZ
Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency25mA @ 120HzBipple Current - High Frequency50mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Capacitance	4.7µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency25mA @ 120HzBipple Current - High Frequency50mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Pockage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency25mA @ 120HzBipple Current - High Frequency50mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	35V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency25mA @ 120HzBipple Current - High Frequency50mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency25mA @ 120HzRipple Current - High Frequency50mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency25mA @ 120HzRipple Current - High Frequency50mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency25mA @ 120HzRipple Current - High Frequency50mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
InInRipple Current - High Frequency50mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	25mA @ 120Hz
Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	50mA @ 10kHz
Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.079" (2.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.197" Dia (5.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.413" (10.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

URZ1V4R7MDD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

URZ1V4R7MDD Payment Methods



URZ1V4R7MDD Shipping Methods



If you have any question about URZ1V4R7MDD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com