



URZ2D151MHD Information



For Reference Only

Part Number URZ2D151MHD

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 150UF 20% 200V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









URZ2D151MHD Specifications

Manufacturer Part NumberURZ2D151MHDManufacturerNichiconCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesURZCapacitance150µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency510mA @ 120HzImpedance-ADATE To be a light of the control of the co
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can URZ Capacitance 150µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Rifetime @ 10kHz Impedance Capacitors Radial, Can URZ LORZ LORZ 150µF -40% Capacitors Capacitors Redial, Can LORZ 150µF 200V Example Current - Low Frequency S10mA @ 120Hz S16mA @ 10kHz Impedance
PackageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesURZCapacitance150μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency510mA @ 120HzRipple Current - High Frequency816mA @ 10kHzImpedance-
PackageRadial, CanSeriesURZCapacitance $150\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $200V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $1000 \text{ Hrs } @ 105^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $510\text{mA} @ 120\text{Hz}$ Ripple Current - High Frequency $816\text{mA} @ 10\text{kHz}$ Impedance-
SeriesURZCapacitance150μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency510mA @ 120HzRipple Current - High Frequency816mA @ 10kHzImpedance-
Capacitance150μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency510mA @ 120HzRipple Current - High Frequency816mA @ 10kHzImpedance-
Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 510mA @ 120Hz Ripple Current - High Frequency 816mA @ 10kHz Impedance -
Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency510mA @ 120HzRipple Current - High Frequency816mA @ 10kHzImpedance-
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency S10mA @ 120Hz Ripple Current - High Frequency 816mA @ 10kHz Impedance -
Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 816mA @ 10kHz Impedance -
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 510mA @ 120Hz Ripple Current - High Frequency 816mA @ 10kHz Impedance -
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 510mA @ 120Hz Ripple Current - High Frequency 816mA @ 10kHz Impedance -
Applications General Purpose Ripple Current - Low Frequency 510mA @ 120Hz Ripple Current - High Frequency 816mA @ 10kHz Impedance -
Ripple Current - Low Frequency 510mA @ 120Hz Ripple Current - High Frequency 816mA @ 10kHz Impedance -
Ripple Current - High Frequency 816mA @ 10kHz Impedance -
Impedance -
2 10 1
Lead Spacing 0.295" (7.50mm)
Size / Dimension 0.709" Dia (18.00mm)
Height - Seated (Max) 1.043" (26.50mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can
Report errors?

URZ2D151MHD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

URZ2D151MHD Payment Methods



















URZ2D151MHD Shipping Methods













If you have any question about URZ2D151MHD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com