



URZ2E101MHD Information



For Reference Only

Part Number URZ2E101MHD

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 100UF 20% 250V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









URZ2E101MHD Specifications

Manufacturer Part Number URZ2E101MHD Manufacturer Nichicon Category Capacitors Package Radial, Can Series URZ Capacitance 100μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - ESR (Equivalent Series Resistance) 1000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 420mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.043" (25.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		
Category Capacitors Package Radial, Can Series URZ Capacitance 100μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 420mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	URZ2E101MHD
Aluminum Electrolytic Capacitors Package Radial, Can URZ Capacitance URZ Capacitance 100µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 420mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	Nichicon
Package Radial, Can Series URZ Capacitance 100μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 420mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series URZ Capacitance 100µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 420mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 100μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 420mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 420mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	URZ
Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency420mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	100μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 420mA @ 120Hz Ripple Current - High Frequency Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 420mA @ 120Hz Ripple Current - High Frequency - Impedance Lead Spacing 0.295" (7.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 1000 Hrs @ 105°C -40°C ~ 105°C -40°	Voltage - Rated	250V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 420mA @ 120Hz Ripple Current - High Frequency - Impedance Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 420mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	1000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 420mA @ 120Hz Ripple Current - High Frequency	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency 420mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing O.295" (7.50mm) Size / Dimension O.709" Dia (18.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	420mA @ 120Hz
Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.709" Dia (18.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	1.043" (26.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

URZ2E101MHD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

URZ2E101MHD Payment Methods



















URZ2E101MHD Shipping Methods













If you have any question about URZ2E101MHD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com