



US681-C00005-015PG Information



For Reference Only

Part Number US681-C00005-015PG

Manufacturer TE Connectivity Measurement Specialties

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR 15PSIG 1/4NPT 4-20MA 2'

Package Cylinde

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









US681-C00005-015PG Specifications

SeriesUS600Pressure TypeVented GaugeOperating Pressure $15 \text{ PSI } (103.42 \text{ kPa})$ Output TypeAnalog CurrentOutput $4 \text{ mA} \sim 20 \text{ mA}$ Accuracy $\pm 0.1\%$ Voltage - Supply $10 \text{ V} \sim 30 \text{ V}$ Port SizeMale - $1/4$ " (6.35mm) NPTPort StyleThreaded		
Category Sensors, Transducers Pressure Sensors, Transducers Package Cylinder Series US600 Pressure Type Vented Gauge Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.1% Voltage - Supply 10 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Features Amplified Output Termination Style Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature - 50°C ~ 125°C Package / Case Supplier Device Package Sensors, Transducers Pressure Sensors, Transducers Nanducers Pressure Sensors, Transducers Pressure Sensors, Transducers Nanducers Pressure Supsort Analog Current 4 mA ~ 20 mA 4 mA ~	Manufacturer Part Number	US681-C00005-015PG
Package Cylinder Series US600 Pressure Type Vented Gauge Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.1% Voltage - Supply 10 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output Termination Style Cable Maximum Pressure 50°C ~ 125°C Package / Case Cylinder Supplier Device Package Cylinder Cylinder Cylinder Cylinder Cylinder Cylinder Cylinder Cylinder Cylinder Cylinder Cylinder Cylinder Cylinder Cylinder Cylinder Cylinder Cylinder Cylinder	Manufacturer	TE Connectivity Measurement Specialties
Package Cylinder Series US600 Pressure Type Vented Gauge Operating Pressure 15 PSI (103.42 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.1% Voltage - Supply 10 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output Termination Style Cable Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -50°C ~ 125°C Package / Case Cylinder Supplier Device Package	Category	Sensors, Transducers
Series US600 Pressure Type Vented Gauge Operating Pressure 15 PSI (103.42 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.1% Voltage - Supply 10 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output Termination Style Cable Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -50°C ~ 125°C Package / Case Cylinder Supplier Device Package		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 15 PSI (103.42 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.1% Voltage - Supply 10 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output Termination Style Cable Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -50°C ~ 125°C Package / Case Cylinder Supplier Device Package	Package	Cylinder
Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.1% Voltage - Supply 10 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output Termination Style Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -50°C ~ 125°C Package / Case Supplier Device Package 15 PSI (103.42 kPa) Analog Current AmAlog Current AmAlog Current 4 mA ~ 20 mA Analog Current 4 mA ~ 20 mA Accuracy 4 mA ~ 20 mA Analog Current 4 mA ~ 20 mA Analog Current 4 mA ~ 20 mA Accuracy 4 mA ~ 20 mA Analog Current 4 mA ~ 20 mA Analog	Series	US600
Output Type Analog Current 4 mA ~ 20 mA Accuracy ±0.1% Voltage - Supply 10 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output Termination Style Cable Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -50°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Pressure Type	Vented Gauge
Output $4 \text{ mA} \sim 20 \text{ mA}$ Accuracy $\pm 0.1\%$ Voltage - Supply $10 \text{ V} \sim 30 \text{ V}$ Port Size $Male - 1/4$ " $(6.35 \text{ mm}) \text{ NPT}$ Port Style $Threaded$ Features $Amplified Output$ Termination Style $Cable$ Maximum Pressure $AE = AE $	Operating Pressure	15 PSI (103.42 kPa)
Accuracy ±0.1% Voltage - Supply 10 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output Termination Style Cable Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -50°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Output Type	Analog Current
Voltage - Supply 10 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output Termination Style Cable Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -50°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Output	4 mA ~ 20 mA
Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output Termination Style Cable Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -50°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Accuracy	±0.1%
Port Style Threaded Features Amplified Output Termination Style Cable Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -50°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Voltage - Supply	10 V ~ 30 V
Features Amplified Output Termination Style Cable Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -50°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Port Size	Male - 1/4" (6.35mm) NPT
Termination Style Cable Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -50°C ~ 125°C Package / Case Cylinder Supplier Device Package	Port Style	Threaded
Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -50°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Features	Amplified Output
Operating Temperature -50°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Termination Style	Cable
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	45 PSI (310.26 kPa)
Supplier Device Package -	Operating Temperature	-50°C ~ 125°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
		Report errors?

US681-C00005-015PG Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

US681-C00005-015PG Payment Methods



















US681-C00005-015PG Shipping Methods













If you have any question about US681-C00005-015PG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com