

# USF1E470MDD

### **USF1E470MDD** Information

www.heisener.com	Part Number Manufacturer Category Description Package	USF1E470MDD Nichicon Capacitors Aluminum Electrolytic Capacitors CAP ALUM 47UF 20% 25V RADIAL Radial, Can For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **USF1E470MDD Specifications**

Manufacturer Part NumberUSFIE470MDDManufacturerNichiconCategoryCapacitorsPackageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUSFCapacitance47µFTolerance±20%Voltage - RatedSVESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplicationsGond A @ 120HzRipple Current - High Frequency500 mOhms
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUSFCapacitance47μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency000 Ant @ 120 HzKipple Current - High Frequency2000 Ant @ 100 KHz
HereinAluminu Electrolytic CapacitorsPackageRadial, CanSeriesUSFCapacitance47μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temperature1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplicationsGond A @ 120HzRippe Current - High Frequency200mA @ 100kHz
PackageRadial, CanSeriesUSFCapacitance47μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplicationsGomA @ 120HzRipple Current - High Frequency200mA @ 100kHz
SeriesUSFCapacitance47μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency100mA @ 120HzRipple Current - High Frequency20mA @ 100kHz
Capacitance47μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency100mA @ 120HzRipple Current - High Frequency20mA @ 100kHz
Tolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency100mA @ 120HzRipple Current - High Frequency200mA @ 100kHz
Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency100mA @ 120HzRipple Current - High Frequency20mA @ 100kHz
ESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency100mA @ 120HzRipple Current - High Frequency200mA @ 100kHz
Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency100mA @ 120HzRipple Current - High Frequency200mA @ 100kHz
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency100mA @ 120HzRipple Current - High Frequency200mA @ 100kHz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency100mA @ 120HzRipple Current - High Frequency200mA @ 100kHz
ApplicationsGeneral PurposeRipple Current - Low Frequency100mA @ 120HzRipple Current - High Frequency200mA @ 100kHz
Ripple Current - Low Frequency100mA @ 120HzRipple Current - High Frequency200mA @ 100kHz
Ripple Current - High Frequency200mA @ 100kHz
Impedance 500 mOhms
r · · · · · ·
Lead Spacing 0.138" (3.50mm)
Size / Dimension 0.315" Dia (8.00mm)
Height - Seated (Max) 0.315" (8.00mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can
Report error

#### **USF1E470MDD Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **USF1E470MDD Payment Methods**



## **USF1E470MDD Shipping Methods**



If you have any question about USF1E470MDD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com