

USH1H330MHD

Request a Quote

USH1H330MHD Information

Heisener.com	Part Number	USH1H330MHD
	Manufacturer	Nichicon
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 33UF 20% 50V RADIAL
	Package	Radial, Can
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



USH1H330MHD Specifications

Manufacturer Part NumberUSH1H330MHDManufacturer QNichiconCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanStriesUSHCapacitance3JuFOberance220%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature90arApplicationsGeneral PurposeApple Current - High Frequency-Liped Acc50°CStrige Current - High Frequency-Liped Acc0.09°T (5.00mm)Size Action Manufacture0.492°D in (12.50mm)Bighe Seated Maxin Seated-Mounting TypeHongh HolePackage Yous-Surface Mount Land Size-Package Yous-Package Yous-Package Yous-Surface Mount Land Size-Package Yous-Package Yous-<	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUSHCapacitance33µFTolerance±0%Voltage - Rated50VESR (Equivalent Series Resistance)-Operating Temperature1000 Hrs @ 85°COperating TemperaturePolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance-Lied Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Pounting TypeFinough HolePokage / CaseMain CanStarder State (Max)Sater (21.00mm)Surface Mount Land Size-Polaring TypeMain CanPolaring TypeSatel (Max)Starder State (Max)Sater (21.00mm)Starder State (Max)Sater (21.00mm)State (Max)Sater (21.00mm)State (State	Manufacturer Part Number	USH1H330MHD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUSHCapacitance33µFTolerance±20%Voltage - RatedSoVESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency0.197" (5.00mm)Siz / Dimension0.492" Dia (12.50mm)Size / Dimension0.827" (21.00mm)Size / Dimension-Auftace Mount Land Size-Mounting TypeFackage / CasePackage / CaseSatial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUSHCapacitance33µFTolerance20%Voltage - Rated50VESR (Equivalent Series Resistance)-Joeranting Temperature1000 Hrs@ 85°COperating Temperature40°C ~ 85°CPolarizationFolareal PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Siz / Dimension0.197" (5.00mm)Siz / Dimension0.492" Dia (12.50mm)Siz / Dimension0.827" (1.100mm)Sirdarea Mount Land Size-Mounting TypeFolarea ManagementPackage / CaseMail, Can	Category	Capacitors
SeriesUSHCapacitance33μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplications6Ripple Current - Low Frequency-Ingedance-Liad Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKaila, Can		Aluminum Electrolytic Capacitors
Capacitance33µFTolerance±20%Voltage Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Ingedance-Liad Spacing0.197" (5.00mm)Size / Dimension0.827" (21.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseStali, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Hight - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Series	USH
Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Argulance-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRadial, Can	Capacitance	33µF
Constraint	Tolerance	±20%
Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Hounting TypeRadia, Can	Voltage - Rated	50V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Anpedance-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Hounting TypeRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 85°C
ApplicationsGeneral PurposeApple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.827" (21.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

USH1H330MHD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

USH1H330MHD Payment Methods



USH1H330MHD Shipping Methods



If you have any question about USH1H330MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com