



USL1H220MDD Information

Heisener.com

Part Number USL1H220MDD

Manufacturer Nichicon Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 22UF 20% 50V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









USL1H220MDD Specifications

Manufacturer Part Number Manufacturer Nichicon Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series USL Capacitance 22µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.138" (3.50mm) Siza / Dimonsion Pica / Occ Commons / Commons		
Category Capacitors Aluminum Electrolytic Capacitors Radial, Can Series USL Capacitance 22µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Inpedance Lead Spacing Capacitors Radial, Can Aluminum Electrolytic Capacitors Radial, Can Capacitors Radial, Can 10SL 20W 10SL 40°C ~ 85°C 65mA @ 120Hz 97.5mA @ 120Hz 10DHz 10DHz	Manufacturer Part Number	USL1H220MDD
PackageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUSLCapacitance22μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency65mA @ 120HzRipple Current - High Frequency97.5mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)	Manufacturer	Nichicon
Package Radial, Can Series USL Capacitance 22µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 97.5mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm)	Category	Capacitors
Series USL Capacitance 22µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency		Aluminum Electrolytic Capacitors
Capacitance 22μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 97.5mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm)	Package	Radial, Can
Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 97.5mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm)	Series	USL
Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 97.5mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm)	Capacitance	22μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 97.5mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm)	Tolerance	±20%
Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 97.5mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm)	Voltage - Rated	50V
Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 97.5mA @ 10kHz Impedance Lead Spacing - Lead Spacing 0.138" (3.50mm)	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 97.5mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm)	Lifetime @ Temp.	1000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 97.5mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm)	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 97.5mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm)	Polarization	Polar
Ripple Current - High Frequency 97.5mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm)	Applications	General Purpose
Impedance - Lead Spacing 0.138" (3.50mm)	Ripple Current - Low Frequency	65mA @ 120Hz
Lead Spacing 0.138" (3.50mm)	Ripple Current - High Frequency	97.5mA @ 10kHz
	Impedance	-
Size / Dimension	Lead Spacing	0.138" (3.50mm)
Size / Difficultion 0.313 Dia (8.00fillit)	Size / Dimension	0.315" Dia (8.00mm)
Height - Seated (Max) 0.315" (8.00mm)	Height - Seated (Max)	0.315" (8.00mm)
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report errors?		Report errors?

USL1H220MDD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

USL1H220MDD Payment Methods





















USL1H220MDD Shipping Methods













If you have any question about USL1H220MDD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com