

USL1H2R2MDD

USL1H2R2MDD Information

	Contact service statisties	Part Number Manufacturer Category Description Package	USL1H2R2MDD Nichicon Capacitors Aluminum Electrolytic Capacitors CAP ALUM 2.2UF 20% 50V RADIAL Radial, Can For the pricing/inventory/lead time, please contact	
	For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



USL1H2R2MDD Specifications

Manufacturer Part NumberUSL1H2R2MDDManufacturer ANichiconCategoryCapacitorsPackageRadial, CanPackageSariesCapacitance2.2µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Liftetime @ Temp.000 Hrs @ 85°COperating Temperature90aarApplicationsGeneral PurposeApplications99harRiple Current - Low Frequency99mA @ 120HzRiple Current - High Frequency0.055° (1.50mm)Size / Dimension0.157° Dia (4.00mm)Hieght - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUSLCapacitance2.2µFTolerance±20%Voltage - Rated5VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs@ 85°COperating Temperature6000 Hrs@ 85°CPolarization6eneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency19mA @ 120HzRipple Current - High Frequency0.55° (1.50mm)Impedance-Lad Spacing0.059° (1.50mm)Siz / Dimension0.157° Dia (4.00mm)Hight - Seated (Max)0.315° (8.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer Part Number	USL1H2R2MDD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUSLCapacitance2.2μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency19mA @ 120HzRipple Current - High Frequency28.5mA @ 10kHzImpedance-Liad Spacing0.059° (1.50mm)Size / Dimension0.157° Dia (4.00mm)Height - Seated (Max)0.315° (8.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer	Nichicon
PackageRadial, CanSeriesUSLCapacitance2.2µFTolerance±0%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature~40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRippe Current - Hugh Frequency19mA @ 120HzInpedance.Lead Spacing0.055" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size.Mounting TypeThrough Hole	Category	Capacitors
SeriesUSLCapacitance2.2µFTolerance±20%Voltage Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRippe Current - Low Frequency19mA @ 120HzRippe Current - High Frequency28.5mA @ 10kHzImpedance-Lead Spacing0.157" Dia (4.00mm)Siz / Dimension0.315" (8.00mm)Height - Seated (Max)-Surface Mount Land Size-Hounting TypeThrough Hole		Aluminum Electrolytic Capacitors
Capacitance2.2µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency19mA @ 120HzImpedance-Liad Spacing0.55° (1.50mm)Size / Dimension0.157° Dia (4.00mm)Height - Seated (Max)0.315° (8.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Package	Radial, Can
Tolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency19mA @ 120HzRippe Current - High Frequency28.5mA @ 10kHzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)3.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Series	USL
Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency19mA @ 120HzBippe Current - High Frequency28.5mA @ 10kHzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)-Surface Mount Land Size-Hounting TypeThrough Hole	Capacitance	2.2µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency19mA @ 120HzRipple Current - High Frequency28.5mA @ 10kHzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Tolerance	±20%
Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency19mA @ 120HzRipple Current - High Frequency28.5mA @ 10kHzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Voltage - Rated	50V
Answission -40°C ~ 85°C Polarization Polar Applications Polar Ripple Current - Low Frequency General Purpose Ripple Current - High Frequency 19mA @ 120Hz Impedance - Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.315" (8.00mm) Surface Mount Land Size - Mounting Type Through Hole	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency19mA @ 120HzRipple Current - High Frequency28.5mA @ 10kHzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Lifetime @ Temp.	1000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency19mA @ 120HzRipple Current - High Frequency28.5mA @ 10kHzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 85^{\circ}\mathrm{C}$
Ripple Current - Low Frequency19mA @ 120HzRipple Current - High Frequency28.5mA @ 10kHzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Polarization	Polar
In a constraint of the second secon	Applications	General Purpose
Impedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - Low Frequency	19mA @ 120Hz
Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - High Frequency	28.5mA @ 10kHz
Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	-
Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Lead Spacing	0.059" (1.50mm)
Surface Mount Land Size-Mounting TypeThrough Hole	Size / Dimension	0.157" Dia (4.00mm)
Mounting Type Through Hole	Height - Seated (Max)	0.315" (8.00mm)
	Surface Mount Land Size	-
Package / Case Radial, Can	Mounting Type	Through Hole
	Package / Case	Radial, Can
Report errors?		Report errors?

USL1H2R2MDD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

USL1H2R2MDD Payment Methods



USL1H2R2MDD Shipping Methods



If you have any question about USL1H2R2MDD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com