

USL1V330MDD

Request a Quote

USL1V330MDD Information

Contraction to the second test	Part Number	USL1V330MDD
	Manufacturer	Nichicon
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 33UF 20% 35V RADIAL
	Package	Radial, Can
		For the pricing/inventory/lead time, please contact
		us
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



USL1V330MDD Specifications

ManufacturerNichiconCapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUSLCapacitance33µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency108mA @ 100HzImpedance-Lied Spacing0.315" Dia (8.00mm)Siz / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Package / CaseKadial, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUSLCapacitance33µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature90arApplicationsGeneral PurposeRipple Current - Low Frequency72mA @ 120HzRipple Current - High Frequency108mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can	Manufacturer Part Number	USL1V330MDD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUSLCapacitance33µFTolerance±20%Voltage - RatedSvESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency108mA @ 10kHzImpedance-Lad Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUSLCapacitance33µFTolerance-20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplications72mA @ 120HzRipple Current - Low Frequency0108 MA @ 10kHzImpedance-Lad Spacing0.138" (3.50mm)Siz / Dimension0.315" Dia (8.00mm)Sirface Mount Land Size-Mounting TypeThrough HolePackage / CaseKaial, Can	Category	Capacitors
NoteUSLCapacitance33μFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency72mA @ 120HzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance33µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency108mA @ 10kHzImpedance-Lead Spacing0.315" Dia (8.00mm)Size / Dimension0.315" Dia (8.00mm)Bright - Seated (Max)-Mounting TypeThrough HolePackage / CaseRadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency72mA @ 120HzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	USL
Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency72mA @ 120HzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Pockage / CaseRatial, Can	Capacitance	33µF
Figure and series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency72mA @ 120HzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency72mA @ 120HzRipple Current - High Frequency108mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	35V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency72mA @ 120HzBipple Current - High Frequency108mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, CanRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency72mA @ 120HzRipple Current - High Frequency108mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency72mA @ 120HzRipple Current - High Frequency108mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40° C ~ 85° C
Ripple Current - Low Frequency72mA @ 120HzRipple Current - High Frequency108mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency108mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	72mA @ 120Hz
Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	108mA @ 10kHz
Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.138" (3.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.315" Dia (8.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.315" (8.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

USL1V330MDD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

USL1V330MDD Payment Methods



USL1V330MDD Shipping Methods



If you have any question about USL1V330MDD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com