

# USP1A101MDD

#### **USP1A101MDD** Information

Heisener.com	Part Number Manufacturer Category Description Package	USP1A101MDD Nichicon Capacitors Aluminum Electrolytic Capacitors CAP ALUM 100UF 20% 10V RADIAL Radial, Can For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **USP1A101MDD Specifications**

ManufacturerNichiconCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUSPCapacitance100µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Operating Temperature2000 Hrs @ 85°COperating Temperature640°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency110mA @ 120HzImpedance-Lead Spacing0.318° (3.50mm)Size / Dimension0.315° Dia (8.00mm)Height - Seated (Max)0.315° NationandSurface Mount Land Size-Mounting TypeThrough Hole		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUSPCapacitance100µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature640°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency110mA @ 120HzImpedance-Lead Spacing0.315" Ga.0mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can	Manufacturer Part Number	USP1A101MDD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUSPCapacitance100µFTolerance±20%Voltage - Rated0VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature2000 Hrs @ 85°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency110mA @ 120HzRipple Current - High Frequency155mA @ 10kHzImpedance-Lead Spacing0.138° (3.50mm)Size / Dimension0.315° Dia (8.00mm)Height - Seated (Max)0.315° Bia (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUSPCapacitance100µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency110mA @ 120HzRipple Current - High Frequency0.315" Gasom)Size / Dimension0.315" Dia (8.00mm)Size / Dimension0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesUSPCapacitance100µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency110mA @ 120HzImpedance-Lad Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKaila, Can		Aluminum Electrolytic Capacitors
Capacitance100μFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency10mA @ 120HzInpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKalia, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency10mA @ 120HzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Series	USP
NotationInterferentVoltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency110mA @ 120HzRipple Current - High Frequency0.138" (3.50mm)Impedance-Lead Spacing0.315" Dia (8.00mm)Size / Dimension0.315" (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Capacitance	100µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationBi-PolarApplicationsGeneral PurposeApple Current - Low Frequency110mA @ 120HzRipple Current - High Frequency165mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency110mA @ 120HzInpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeFackage / CaseRakage / CaseRadial, Can	Voltage - Rated	10V
Operating Temperature-40°C ~ 85°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency110mA @ 120HzRipple Current - High Frequency165mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max).Surface Mount Land Size-Mounting TypeFunculationPackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency110mA @ 120HzRipple Current - High Frequency165mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency110mA @ 120HzRipple Current - High Frequency165mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency110mA @ 120HzRipple Current - High Frequency165mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Bi-Polar
Ripple Current - High Frequency165mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	110mA @ 120Hz
Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	165mA @ 10kHz
Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.138" (3.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.315" Dia (8.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.315" (8.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### **USP1A101MDD Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **USP1A101MDD Payment Methods**



### **USP1A101MDD Shipping Methods**



If you have any question about USP1A101MDD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com