

# USP1E4R7MDD1TP

### **USP1E4R7MDD1TP Information**

Heisener.com

Part Number USP1E4R7MDD1TP

Manufacturer Nichicon
Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 4.7UF 20% 25V RADIAL

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **USP1E4R7MDD1TP Specifications**

Manufacturer Part Number         USPIE4R7MDDITP           Manufacturer         Nichicon           Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can           Series         USP           Capacitance         4.7µF           Tolerance         ±20%           Voltage - Rated         25V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Bi-Polar           Applications         General Purpose           Ripple Current - Low Frequency         21mA @ 120Hz           Ripple Current - High Frequency         31.5mA @ 10kHz           Impedance         -           Lead Spacing         0.079" (2.00mm)           Size / Dimension         0.197" Dia (5.00mm)           Height - Seated (Max)         0.315" (8.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	•	
Category         Capacitors           Package         Radial, Can           Series         USP           Capacitance         4.7μF           Tolerance         ±20%           Voltage - Rated         25V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Bi-Polar           Applications         General Purpose           Ripple Current - Low Frequency         21mA @ 120Hz           Ripple Current - High Frequency         31.5mA @ 10kHz           Impedance         -           Lead Spacing         0.079" (2.00mm)           Size / Dimension         0.197" Dia (5.00mm)           Height - Seated (Max)         0.315" (8.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer Part Number	USP1E4R7MDD1TP
Package         Radial, Can           Series         USP           Capacitance         4.7μF           Tolerance         ±20%           Voltage - Rated         25V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Bi-Polar           Applications         General Purpose           Ripple Current - Low Frequency         21mA @ 120Hz           Ripple Current - High Frequency         31.5mA @ 10kHz           Impedance         -           Lead Spacing         0.079" (2.00mm)           Size / Dimension         0.197" Dia (5.00mm)           Height - Seated (Max)         0.315" (8.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer	Nichicon
Package         Radial, Can           Series         USP           Capacitance         4.7μF           Tolerance         ±20%           Voltage - Rated         25V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Bi-Polar           Applications         General Purpose           Ripple Current - Low Frequency         21mA @ 120Hz           Ripple Current - High Frequency         31.5mA @ 10kHz           Impedance         -           Lead Spacing         0.079" (2.00mm)           Size / Dimension         0.197" Dia (5.00mm)           Height - Seated (Max)         0.315" (8.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Category	Capacitors
Series         USP           Capacitance         4.7μF           Tolerance         ±20%           Voltage - Rated         25V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Bi-Polar           Applications         General Purpose           Ripple Current - Low Frequency         21mA @ 120Hz           Ripple Current - High Frequency         31.5mA @ 10kHz           Impedance         -           Lead Spacing         0.079" (2.00mm)           Size / Dimension         0.197" Dia (5.00mm)           Height - Seated (Max)         0.315" (8.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		Aluminum Electrolytic Capacitors
Capacitance         4.7μF           Tolerance         ±20%           Voltage - Rated         25V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Bi-Polar           Applications         General Purpose           Ripple Current - Low Frequency         21mA @ 120Hz           Ripple Current - High Frequency         31.5mA @ 10kHz           Impedance         -           Lead Spacing         0.079" (2.00mm)           Size / Dimension         0.197" Dia (5.00mm)           Height - Seated (Max)         0.315" (8.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 25V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C  Operating Temperature -40°C ~ 85°C  Polarization Bi-Polar  Applications General Purpose Ripple Current - Low Frequency 21mA @ 120Hz  Ripple Current - High Frequency 31.5mA @ 10kHz  Impedance - Lead Spacing 0.079" (2.00mm)  Size / Dimension 0.197" Dia (5.00mm)  Heigh - Seated (Max) 0.315" (8.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Series	USP
Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency21mA @ 120HzRipple Current - High Frequency31.5mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	4.7μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Bi-Polar  Applications  General Purpose  Ripple Current - Low Frequency  21mA @ 120Hz  Ripple Current - High Frequency  31.5mA @ 10kHz  Impedance  -  Lead Spacing  0.079" (2.00mm)  Size / Dimension  0.197" Dia (5.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 85°C  Polarization  Bi-Polar  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  31.5mA @ 120Hz  Impedance  - Lead Spacing  0.079" (2.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  2000 Hrs @ 85°C  -40°C ~ 85°C  Bi-Polar  General Purpose  21mA @ 120Hz  31.5mA @ 10kHz  -  0.079" (2.00mm)  0.197" Dia (5.00mm)  Through Hole  Radial, Can	Voltage - Rated	25V
Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 31.5mA @ 120Hz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.315" (8.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Bi-Polar  Applications General Purpose  Ripple Current - Low Frequency 21mA @ 120Hz  Ripple Current - High Frequency 31.5mA @ 10kHz  Impedance -  Lead Spacing 0.079" (2.00mm)  Size / Dimension 0.197" Dia (5.00mm)  Height - Seated (Max) 0.315" (8.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications  General Purpose  Ripple Current - Low Frequency  21mA @ 120Hz  Ripple Current - High Frequency  31.5mA @ 10kHz  Impedance  - Lead Spacing  0.079" (2.00mm)  Size / Dimension  0.197" Dia (5.00mm)  Height - Seated (Max)  0.315" (8.00mm)  Surface Mount Land Size  -  Mounting Type  Through Hole  Package / Case  Radial, Can	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  31.5mA @ 10kHz  Impedance  - Lead Spacing  0.079" (2.00mm)  Size / Dimension  0.197" Dia (5.00mm)  Height - Seated (Max)  0.315" (8.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Polarization	Bi-Polar
Ripple Current - High Frequency Impedance	Applications	General Purpose
Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	21mA @ 120Hz
Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	31.5mA @ 10kHz
Size / Dimension 0.197" Dia (5.00mm)  Height - Seated (Max) 0.315" (8.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.079" (2.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.197" Dia (5.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.315" (8.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
Report crisis.		Report errors?

#### **USP1E4R7MDD1TP Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **USP1E4R7MDD1TP Payment Methods**





















### **USP1E4R7MDD1TP Shipping Methods**













If you have any question about USP1E4R7MDD1TP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com