



# **USR0J330MDD** Information



For Reference Only

Part Number USR0J330MDD

Manufacturer Nichicon Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 33UF 20% 6.3V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **USR0J330MDD Specifications**

Manufacturer Part Number         USR0J330MDD           Manufacturer         Nichicon           Category         Capacitors           Package         Aluminum Electrolytic Capacitors           Package         Radial, Can           Series         USR           Capacitance         33µF           Tolerance         ±20%           Voltage - Rated         6.3V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         40°C ~ 85°C           Polarization         General Purpose           Ripple Current - Low Frequency         40mA @ 120Hz           Ripple Current - High Frequency         -           Lead Spacing         0.059" (1.50mm)           Size / Dimension         0.157" Dia (4.00mm)           Height - Seated (Max)         0.315" (8.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		
Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can           Series         USR           Capacitance         33µF           Tolerance         ±20%           Voltage - Rated         6.3V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         40mA @ 120Hz           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         0.059" (1.50mm)           Size / Dimension         0.157" Dia (4.00mm)           Height - Seated (Max)         0.315" (8.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer Part Number	USR0J330MDD
PackageRadial, CanSeriesUSRCapacitance33µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency40mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	Nichicon
Package         Radial, Can           Series         USR           Capacitance         33µF           Tolerance         ±20%           Voltage - Rated         6.3V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         40mA @ 120Hz           Ripple Current - High Frequency         -           Lead Spacing         0.059" (1.50mm)           Size / Dimension         0.157" Dia (4.00mm)           Height - Seated (Max)         0.315" (8.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Category	Capacitors
Series         USR           Capacitance         33µF           Tolerance         ±20%           Voltage - Rated         6.3V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         40mA @ 120Hz           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         0.059" (1.50mm)           Size / Dimension         0.157" Dia (4.00mm)           Height - Seated (Max)         0.315" (8.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		Aluminum Electrolytic Capacitors
Capacitance33µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency40mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 6.3V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C  Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose Ripple Current - Low Frequency 40mA @ 120Hz  Ripple Current - High Frequency - Impedance - Lead Spacing 0.059" (1.50mm)  Size / Dimension 0.157" Dia (4.00mm)  Height - Seated (Max) 0.315" (8.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Raisian Cassian -  Raisial, Can	Series	USR
Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency40mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	33μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  40mA @ 120Hz  Ripple Current - High Frequency  Impedance  - Lead Spacing  30.059" (1.50mm)  Size / Dimension  0.157" Dia (4.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Apple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  2000 Hrs @ 85°C  -40°C ~ 85°C  Polar  -40°C ~ 85°C  -40°C ~ 80°C	Voltage - Rated	6.3V
Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Polar  Ripple Current - High Frequency Polar  Ripple Current - High Frequency Polar  Impedance Polar  Impedance Polar  Po	ESR (Equivalent Series Resistance)	-
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 40mA @ 120Hz  Ripple Current - High Frequency -  Impedance -  Lead Spacing 0.059" (1.50mm)  Size / Dimension 0.157" Dia (4.00mm)  Height - Seated (Max) 0.315" (8.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications  Ripple Current - Low Frequency  40mA @ 120Hz  Ripple Current - High Frequency  - Impedance  Lead Spacing  5ize / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  Radial, Can	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency 40mA @ 120Hz  Ripple Current - High Frequency - Impedance - Lead Spacing 0.059" (1.50mm)  Size / Dimension 0.157" Dia (4.00mm)  Height - Seated (Max) 0.315" (8.00mm)  Surface Mount Land Size - Mounting Type Through Hole  Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency - Impedance - Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.315" (8.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	40mA @ 120Hz
Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.157" Dia (4.00mm)  Height - Seated (Max) 0.315" (8.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.059" (1.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.157" Dia (4.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.315" (8.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### **USR0J330MDD Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **USR0J330MDD Payment Methods**



















### **USR0J330MDD Shipping Methods**













If you have any question about USR0J330MDD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com