

UST0J470MDD

Request a Quote

UST0J470MDD Information

	Part Number	UST0J470MDD
	Manufacturer	Nichicon
www.heisener.com	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 47UF 20% 6.3V RADIAL
	Package	Radial, Can
		For the pricing/inventory/lead time, please contact
		us
For Reference Only		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UST0J470MDD Specifications

Manufacturer Part NumberUST01470MDDManufacturer ANichiconCategoryCapacitorsAtminum Electrolytic CapacitorsPackageRadial, CanSeriesUSTCapacitance4/µFTolerance220%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature90arApplications5°C ~ 105°CPolarization6General PurposeApple Current - High Frequency5°M A @ 120HzNighe Current - High Frequency079°C 200mn)Size Afound Land Size-Surface Mount Land Size-Mounting Type-Polarized Mount Land Size-Package Case-Runger Chase-Surface Mount Land Size-Package Case-Package Case- <t< th=""><th>-</th><th></th></t<>	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUSTCapacitance4/µFTolerance5/0%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Derating Temperature1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRippe Current - High Frequency50mA @ 120HzImpedance-Lad Spacing0.197° (2.00mm)Size / Dimension0.197° Dia (5.00mm)Hight - Seated (Max)0.315° (8.00mm)Surface Mount Land Size-Anuning TypeFinough HolePokage / CaseManagementPackage / CaseKadia, Can	Manufacturer Part Number	UST0J470MDD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUSTCapacitance47µFTolerance=20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature>55°C ~ 105°CPolarizationGeneral PurposeApplicationsSom A @ 120HzRipple Current - Low Frequency50m A @ 120HzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Sirafe Mount Land Size-Mounting TypeFacuage / CaseRokage / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUSTCapacitance47µFTolerance20%Voltage - Rated6.3VESR (Equivalent Series Resistance)000 Hrs @ 105°COperating Temperature000 Hrs @ 105°COperating Temperature55°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency50mA @ 100HzRipple Current - High Frequency000 Hrs @ 100HzImpedance-Lad Spacing0.107" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Size / Dimension0.31" (8.00mm)Hight - Seated (Max)-Surface Mount Land Size-Mounting TypeMaid, Can	Category	Capacitors
SeriesUSTCapacitance47μFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplicationsGoneral PurposeRippe Current - Low Frequency50mA @ 120HzImpedance-Lead Spacing0.197° Dia (5.00mm)Size / Dimension0.197° Dia (5.00mm)Surface Mount Land Size-Munting TypeThrough HolePokange / CaseMail Agan		Aluminum Electrolytic Capacitors
Capacitance47µFTolerance±20%Voltage Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency50mA @ 100 HrzImpedance-Lad Spacing0.197° (2.00mm)Size / Dimension0.197° Dia (5.00mm)Sirafe Mount Land Size-Mounting Type-Polarizet Conservert-Strafe Mount Land Size-Mounting TypeFrequencyPolarizet Conservert-Strafe Mount Land Size-Polarizet Conservert-Strafe Conservert-Strafe Mount Land Size-Polarizet Conservert-Strafe Mount Land Size-Polarizet Conservert-Polarizet Conservert-Strafe Mount Land Size-Polarizet Conservert-Polarizet Conservert-Polari	Package	Radial, Can
Tolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarPolarApplicationsGeneral PurposeRipple Current - High Frequency50mA @ 120HzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Bight - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Series	UST
Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency50mA @ 120HzRipple Current - High Frequency0.079" (2.00mm)Impedance-Lead Spacing0.197" Dia (5.00mm)Size / Dimension0.315" (8.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeRadial, Can	Capacitance	47µF
ConstructionESR (Equivalent Series Resistance)-ESR (Equivalent Series Resistance)1000 Hrs @ 105°CLifetime @ Temp.000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency50mA @ 120HzMipedance-Lead Spacing0.079° (2.00mm)Size / Dimension0.197° Dia (5.00mm)Height - Seated (Max)0.315° (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency50mA @ 120HzRipple Current - High Frequency75mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadia, CanRadia, Can	Voltage - Rated	6.3V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency50mA @ 120HzBrippe Current - High Frequency75mA @ 10kHzImpedance-Lead Spacing0.079° (2.00mm)Size / Dimension0.197° Dia (5.00mm)Height - Seated (Max)0.315° (8.00mm)Surface Mount Land Size-Hounting TypeRadia, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency50mA @ 120HzRipple Current - High Frequency75mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 105°C
ApplicationsGeneral PurposeApplications50mA @ 120HzRipple Current - Low Frequency50mA @ 10kHzMipedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadia, Can	Operating Temperature	$-55^{\circ}C \sim 105^{\circ}C$
Ripple Current - Low Frequency50mA @ 120HzRipple Current - High Frequency75mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency75mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	50mA @ 120Hz
Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.315" (8.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	75mA @ 10kHz
Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.079" (2.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.197" Dia (5.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.315" (8.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UST0J470MDD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UST0J470MDD Payment Methods



UST0J470MDD Shipping Methods



If you have any question about UST0J470MDD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com