

# UST1E100MDD

Request a Quote

### **UST1E100MDD** Information

www.neisener.com	Part Number Manufacturer Category	UST1E100MDD Nichicon Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 10UF 20% 25V RADIAL	
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **UST1E100MDD Specifications**

ManufacturerNichiconCapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUSTCapacitance10µFTolerance±20%Voltage - Rated55°C ~ 105°CESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance0.079° (2.00mm)Size / Dimension0.197° Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUSTCapacitance10µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating TemperaturePolarApplicationsGeneral PurposeRipple Current - Low Frequency3mA @ 120HzRipple Current - High Frequency-Lied Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)3.15" (8.00mm)Surface Mount Land Size-Package / CaseKadia, Can	Manufacturer Part Number	UST1E100MDD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUSTCapacitance10µFTolerance±20%Voltage - RatedSvESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lad Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUSTCapacitance10µFTolerance±20%Voltage - Rated5vESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplications33mA @ 120HzRipple Current - High Frequency0.007° (2.00mm)Siz / Dimension0.197° Dia (5.00mm)Siz / Dimension0.197° Dia (5.00mm)Sirface Mount Land Size-Mounting TypeHolePackage / CaseKalial, Can	Category	Capacitors
SeriesUSTCapacitance10μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Bight - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
CapacitanceI0µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature>55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.079° (2.00mm)Size / Dimension0.197° Dia (5.00mm)Height - Seated (Max)0.315° (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency33mA @ 120HzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	UST
Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency33mA @ 120HzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Pockage / CaseRadial, Can	Capacitance	10µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency33mA @ 120HzBipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency33mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can	Voltage - Rated	25V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency33mA @ 120HzBipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency33mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency33mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency33mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In PropositionInternational PropositionRipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	33mA @ 120Hz
Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.079" (2.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.197" Dia (5.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.315" (8.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### **UST1E100MDD Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **UST1E100MDD Payment Methods**



## **UST1E100MDD Shipping Methods**



If you have any question about UST1E100MDD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com