

# UST1HR47MDD

Request a Quote

### **UST1HR47MDD Information**

	Part Number	UST1HR47MDD
www.husener.com	Manufacturer	Nichicon
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 0.47UF 20% 50V RADIAL
	Package	Radial, Can
		For the pricing/inventory/lead time, please contact
		us
For Reference Only		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **UST1HR47MDD Specifications**

Manufacturer Part Number UST1HR47MDD   Manufacturer Nichicon   Category Capacitors   Atuminum Electrolytic Capacitors Atuminum Electrolytic Capacitors   Package Radial, Can   Series UST   Capacitance 0.47 µF   Tolerance ±20%   Voltage - Rated 50V   ESR (Equivalent Series Resistance) -   Lifetime @ Temp. 1000 Hrs @ 105°C   Operating Temperature -55°C ~ 105°C   Polarization General Purpose   Applications General Purpose   Ripple Current - Low Frequency 5mA @ 120Hz   Impedance -   Lead Spacing 0.55° (1.50mm)   Size / Dimension 0.55° (8.00mm)   Height - Seated (Max) 0.55° (8.00mm)   Size / Dimension 0.515° (8.00mm)   Kurige Xeature (Max) 0.315° (8.00mm)   Surface Mount Land Size -   Apached Size -   Mounting Type Through Hole	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUSTCapacitance0.47µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRippe Current - High Frequency55°C 105 MLImpedance-Liad Spacing500 MLSize / Dimension0.059°(1.50m)Size / Dimension0.157° Dia (4.00mm)Height - Seated (Max)0.315° (8.00mm)Surface Mount Land Size-Nounting TypeFrough HolePackage / CaseKadia, Can	Manufacturer Part Number	UST1HR47MDD
Auminum Electrolytic CapacitorsPackageRadial, CanSeriesUSTCapacitance0.47µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency5mA @ 120HzRipple Current - High Frequency0.55° (1.50mm)Size / Dimension0.515° (1.50mm)Size / Dimension0.515° (1.50mm)Size / Dimension0.515° (1.50mm)Kurface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUSTCapacitance0.47µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplications5mA @ 120HzRipple Current - Low Frequency5mA @ 120HzImpedance-Lead Spacing0.55°T i Si (A.00mm)Size / Dimension0.157" Dia (4.00mm)Size / Dimension3.15" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesUSTCapacitance0.47µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature>55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRippe Current - Low Frequency5mA @ 120HzImpedance-Lead Spacing0.059° (1.50mm)Size / Dimension0.157° Dia (4.00mm)Height - Seated (Max)3.15° (8.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseKaila (Can		Aluminum Electrolytic Capacitors
Capacitance0.47µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-S5°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency5.5M @ 100 Hrs @ 102 HrzImpedance-Liad Spacing0.55° (1.50°m)Size / Dimension0.157° Dia (4.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatia, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency5mA @ 120HzImpedance-Lead Spacing0.059° (1.50mm)Size / Dimension0.157° Dia (4.00mm)Bight - Seated (Max)0.315° (8.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can	Series	UST
Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.059°(1.50mm)Size / Dimension0.157° Dia (4.00mm)Height - Seated (Max)0.315° (8.00mm)Surface Mount Land Size-Hounting TypeFrequenctPackage / CaseRatial, Can	Capacitance	0.47µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarPolarApplicationsGeneral PurposeRipple Current - Low Frequency5mA @ 120HzRippe Current - High Frequency7.5mA @ 10kHzImpedance-Lead Spacing0.055° (1.50mm)Size / Dimension0.157° Dia (4.00mm)Height - Seated (Max)0.315° (8.00mm)Surface Mount Land Size-Hounting TypeForage (Case)Package / CaseRadia, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5mA @ 120HzRipple Current - High Frequency7.5mA @ 10kHzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeRadial, Can	Voltage - Rated	50V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5mA @ 120HzRipple Current - High Frequency7.5mA @ 10kHzImpedance-Lead Spacing0.059° (1.50mm)Size / Dimension0.157° Dia (4.00mm)Height - Seated (Max)0.315° (8.00mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, CanRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5mA @ 120HzRipple Current - High Frequency7.5mA @ 10kHzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency5mA @ 120HzRipple Current - High Frequency7.5mA @ 10kHzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency5mA @ 120HzRipple Current - High Frequency7.5mA @ 10kHzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of the first	Applications	General Purpose
Impedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	5mA @ 120Hz
Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	7.5mA @ 10kHz
Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.059" (1.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.157" Dia (4.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.315" (8.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can
		Report errors?

#### **UST1HR47MDD** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **UST1HR47MDD** Payment Methods



## **UST1HR47MDD Shipping Methods**



If you have any question about UST1HR47MDD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com