



UST1V330MDD Information



For Reference Only

Part Number UST1V330MDD

Manufacturer Nichicon Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 33UF 20% 35V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UST1V330MDD Specifications

Manufacturer Part Number Manufacturer Nichicon Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series UST Capacitance 33µF Tolerance ±20% Voltage - Rated 55V ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -55°C ~ 105°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing O1138" (3.50mm)	<u> </u>	
Category Category Capacitors Aluminum Electrolytic Capacitors Radial, Can Series UST Capacitance 33µF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Lied Spacing Capacitors Aluminum Electrolytic Capacitors Radial, Can LUST 20% Capacitans 100T 20% 600 600 600 600 600 600 600 600 600 6	Manufacturer Part Number	UST1V330MDD
PackageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUSTCapacitance33μFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency72mA @ 120HzRipple Current - High Frequency108mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)	Manufacturer	Nichicon
PackageRadial, CanSeriesUSTCapacitance33μFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency72mA @ 120HzRipple Current - High Frequency108mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)	Category	Capacitors
SeriesUSTCapacitance33μFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency72mA @ 120HzRipple Current - High Frequency108mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)		Aluminum Electrolytic Capacitors
Capacitance33μFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency72mA @ 120HzRipple Current - High Frequency108mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)	Package	Radial, Can
Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 72mA @ 120Hz Ripple Current - High Frequency 108mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm)	Series	UST
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Inmedance Lead Spacing 35V	Capacitance	33μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 108mA @ 10kHz Impedance Lead Spacing - Lead Spacing 0.138" (3.50mm)	Tolerance	±20%
Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 72mA @ 120Hz Ripple Current - High Frequency 108mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm)	Voltage - Rated	35V
Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 108mA @ 10kHz Impedance Lead Spacing - Lead Spacing -55°C ~ 105°C Polar Polar 108mA @ 10kHz 108mA @ 10kHz	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 72mA @ 120Hz Ripple Current - High Frequency 108mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm)	Lifetime @ Temp.	1000 Hrs @ 105°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency 108mA @ 10kHz Impedance Lead Spacing O.138" (3.50mm)	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency 108mA @ 10kHz Impedance Lead Spacing 0.138" (3.50mm)	Polarization	Polar
Ripple Current - High Frequency 108mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm)	Applications	General Purpose
Impedance - Lead Spacing 0.138" (3.50mm)	Ripple Current - Low Frequency	72mA @ 120Hz
Lead Spacing 0.138" (3.50mm)	Ripple Current - High Frequency	108mA @ 10kHz
	Impedance	-
0.712 0.00	Lead Spacing	0.138" (3.50mm)
Size / Dimension U.315" Dia (8.00mm)	Size / Dimension	0.315" Dia (8.00mm)
Height - Seated (Max) 0.315" (8.00mm)	Height - Seated (Max)	0.315" (8.00mm)
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report errors?		Report errors?

UST1V330MDD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UST1V330MDD Payment Methods



















UST1V330MDD Shipping Methods













If you have any question about UST1V330MDD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com