

USW1C101MDD

Request a Quote

USW1C101MDD Information

	Part Number	USW1C101MDD
www.heisener.com	Manufacturer	Nichicon
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 100UF 20% 16V RADIAL
	Package	Radial, Can
V		For the pricing/inventory/lead time, please contact us
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



USW1C101MDD Specifications

ManufacturerNichiconCatagoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUSWCapacitance100µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature90arApplicationsAudioRipple Current - High Frequency98mA @ 120HzRipple Current - High Frequency0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUSWCapacitance100µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency98mA @ 120HzImpedance-Lied Spacing0.098° (2.50mm)Size / Dimension0.248° Dia (6.30mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Package / CaseRatia, Can	Manufacturer Part Number	USW1C101MDD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUSWCapacitance100µFTolerance±20%Voltage - Rated6VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarization9kmA @ 120HzRipple Current - Low Frequency98mA @ 120HzRipple Current - High Frequency0.098° (2.50mm)Size / Dimension0.248° Dia (6.30mm)Size / Dimension0.315° (8.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUSWCapacitance100µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsSmA @ 120HzRipple Current - Low Frequency98mA @ 120HzImpedance-Lad Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Size / Dimension0.315" (8.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Category	Capacitors
SeriesUSWCapacitance100µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency98mA @ 120HzInpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Package / CaseRatial, Can		Aluminum Electrolytic Capacitors
Capacitance100µFTolerance±20%Voltage - Rated6VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency98mA @ 120HzInpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)-Surface Mount Land Size-Pounting TypeThrough HolePackage / CaseRidal, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency98mA @ 120HzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Package / CaseRatial, Can	Series	USW
Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency98mA @ 120HzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Capacitance	100µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency98mA @ 120HzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency98mA @ 120HzBipple Current - High Frequency147mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max).Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	16V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency98mA @ 120HzRipple Current - High Frequency147mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Package / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsAudioRipple Current - Low Frequency98mA @ 120HzRipple Current - High Frequency147mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 85°C
ApplicationsAudioRipple Current - Low Frequency98mA @ 120HzRipple Current - High Frequency147mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 85°C
InPart of the second secon	Polarization	Polar
InInRipple Current - High Frequency147mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	Audio
Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	98mA @ 120Hz
Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	147mA @ 10kHz
Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.248" Dia (6.30mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.315" (8.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

USW1C101MDD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

USW1C101MDD Payment Methods



USW1C101MDD Shipping Methods



If you have any question about USW1C101MDD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com