

# USW1H100MDD

Request a Quote

### **USW1H100MDD** Information

\	Part Number	USW1H100MDD	
www.heisener.com	Manufacturer	Nichicon	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 10UF 20% 50V RADIAL	
	Package	Radial, Can	
V		For the pricing/inventory/lead time, please contact	
		us	
For Reference Only		Website: https://www.heisener.com	
		E-mail: salesdept@heisener.com	

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **USW1H100MDD Specifications**

ManufacturerNichiconCagacitorsAluminum Electrolytic CagacitorsPackageRadial, CanPackageRadial, CanSeriesUSWCapacitance10µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature90arApplicationsAduioRipple Current - Low FrequencySmA @ 120HzRipple Current - High Frequency57mA @ 10kHzImpedance-Lied Spacing0.079° (2.00mm)Size / Dimension0.197° Dia (5.00mm)Height - Seated (Max)3.15° (8.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageRadial, CanSeriesUSWCapacitance10µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsSmA @ 120HzRipple Current - Low Frequency57mA @ 10kHzImpedance-Lead Spacing0.079° (2.00mm)Size / Dimension0.197° Dia (5.00mm)Height - Seated (Max)0.315° (8.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer Part Number	USW1H100MDD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUSWCapacitance10µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationAudioRipple Current - Low FrequencySmA @ 120HzRipple Current - High Frequency57mA @ 10kHzImpedance-Lad Spacing0.079° (2.00mm)Siz / Dimension0.197° Dia (5.00mm)Sirace Mount Land Size-Mounting TypeFinough HolePackage / CaseStail, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUSWCapacitance10µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationAudioApplicationsSmA @ 120HzRipple Current - How Frequency57mA @ 10kHzRipple Current - High Frequency0.079" (2.00mm)Siz / Dimension0.197" Dia (5.00mm)Siz / Dimension0.315" (8.00mm)Surface Mount Land Size-Mounting TypeHolePackage / CaseKadia, Can	Category	Capacitors
SeriesUSWCapacitance10μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency38mA @ 120HzRipple Current - High Frequency57mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can		Aluminum Electrolytic Capacitors
Capacitance10µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency38mA @ 120HzInpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Polaring TypeFrough HolePackage / CaseKaila, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency38mA @ 120HzBipple Current - High Frequency57mA @ 10kHzImpedance-Lead Spacing0.079° (2.00mm)Size / Dimension0.197° Dia (5.00mm)Hight - Seated (Max)0.315° (8.00mm)Surface Mount Land Size-Package / CaseRatial, Can	Series	USW
Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency38mA @ 120HzBrippe Current - High Frequency57mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land SizeFrough HolePackage / CaseRatial, Can	Capacitance	10µF
ComponentESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency38mA @ 120HzBipple Current - High Frequency57mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Pockage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency38mA @ 120HzBripple Current - High Frequency57mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can	Voltage - Rated	50V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency38mA @ 120HzRipple Current - High Frequency57mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsAudioRipple Current - Low Frequency38mA @ 120HzRipple Current - High Frequency57mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 85°C
ApplicationsAudioRipple Current - Low Frequency38mA @ 120HzRipple Current - High Frequency57mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 85°C
InInRipple Current - Low Frequency38mA @ 120HzRipple Current - High Frequency57mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
InInRipple Current - High Frequency57mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	Audio
Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	38mA @ 120Hz
Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	57mA @ 10kHz
Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.079" (2.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.197" Dia (5.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.315" (8.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### **USW1H100MDD Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **USW1H100MDD Payment Methods**



## **USW1H100MDD** Shipping Methods



If you have any question about USW1H100MDD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com