

# UTM1A221MPD

Request a Quote

## **UTM1A221MPD Information**

Heisener.com	Part Number	UTM1A221MPD	
	Manufacturer	Nichicon	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 220UF 20% 10V RADIAL	
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **UTM1A221MPD Specifications**

Manufacturer Part NumberUTM1A221MPDManufacturer ANichiconCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUTMCapacitance20µFTolerance20µFVoltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ S5°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Lipdace0.197° (5.00mm)Sized (Max)0.394° Dia(10.00mm)Sized (Max)0.827° (21.00mm)Surface Mount Land Size-Auring TypePincugh HelePincage Munut Land Size-Surface Mount Land Size-Anone Munut Surge Compose-Surface Mount Land Size-Auring Type-Pince Munut Surge Compose-Surface Mount Land Size-Anone Munut Surge Compose-Surface Mount Land Size-Auring Type-Pince Mount Surge Compose-Surge Munut Surge Compose-	•	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUTMCapacitance20µFTolerance420%Voltage - Rated10VESR (Equivalent Series Resistance)-Operating Temperature9000 Hrs@ 85°COperating Temperature0000 Hrs@ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.327" (21.00mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRadia, Can	Manufacturer Part Number	UTM1A221MPD
Auminum Electrolytic CapacitorsPackageRadial, CanSeriesUTMCapacitance220µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance0197" (5.00mm)Siz / Dimension0.394" Dia (10.00mm)Size / Dimension0.327" (21.00mm)Hight - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Polaring TypeRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUTMCapacitance20µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Lined Spacing0.197" (5.00mm)Siz / Dimension0.394" Dia (10.00mm)Siz / Dimension0.394" Dia (10.00mm)Sirder Mount Land Size-Mounting TypeHorage HalePackage / CaseStala, Can	Category	Capacitors
SeriesUTMCapacitance220µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Ingedance-Liad Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseKadia Can		Aluminum Electrolytic Capacitors
Capacitance20μFTolerance±20%Voltage Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance-Liad Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Mounting TypeRidai, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Size / Dimension0.827" (21.00mm)Munting TypeFinough HolePourting Temperature-Ripple Current Law Size (Max)0.827" (21.00mm)Size / Dimension-Surface Mount Land Size-Rutage / Case-Rekage / Case-	Series	UTM
Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime G Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency-Argulance-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRatial, Can	Capacitance	220µF
Constraint-ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Kipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Hounting TypeFough HolePackage / CaseRadia, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.827" (21.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeRadial, Can	Voltage - Rated	10V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Hight - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Hounting TypeRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadia, Can	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.827" (21.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.827" (21.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can
		Report errors?

### **UTM1A221MPD Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### **UTM1A221MPD Payment Methods**



# **UTM1A221MPD Shipping Methods**



If you have any question about UTM1A221MPD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com