



UTS012D4S Information

www.he

Part Number UTS012D4S Manufacturer Souriau

Category Connectors, Interconnects Circular Connectors

Description CONN RCPT SQ FLNG 4POS W/SKT PCB

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UTS012D4S Specifications

Manufacturer Part Number UTS012D4S Manufacturer Souriau Category Connectors, Interconnects Package - Series Trim Trio? UTS Hi Seal Connector Type Receptacle, Female Sockets Number of Positions 4 (3 + PE) Shell Size - Insert 12-4 Shell Size, MIL - Mounting Type Panel Mount, Flange; Through Hole Termination Solder Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 500V Current Rating 10A			
CategoryConnectors, InterconnectsPackage-SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Female SocketsNumber of Positions4 (3 + PE)Shell Size - Insert12-4Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated500VCurrent Rating10A	Manufacturer Part Number	UTS012D4S	
Package-SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Female SocketsNumber of Positions4 (3 + PE)Shell Size - Insert12-4Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated500VCurrent Rating10A	Manufacturer	Souriau	
Package-SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Female SocketsNumber of Positions4 (3 + PE)Shell Size - Insert12-4Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated500VCurrent Rating10A	Category	Connectors, Interconnects	
SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Female SocketsNumber of Positions4 (3 + PE)Shell Size - Insert12-4Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated500VCurrent Rating10A		Circular Connectors	
Connector Type Receptacle, Female Sockets Number of Positions 4 (3 + PE) Shell Size - Insert 12-4 Shell Size, MIL - Mounting Type Panel Mount, Flange; Through Hole Termination Solder Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Gold Features - Contact Finish Gold Features - Solov Current Rating 10A	Package	-	
Number of Positions4 (3 + PE)Shell Size - Insert12-4Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated500VCurrent Rating10A	Series	Trim Trio? UTS Hi Seal	
Shell Size - Insert12-4Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated500VCurrent Rating10A	Connector Type	Receptacle, Female Sockets	
Shell Size, MIL Mounting Type Panel Mount, Flange; Through Hole Termination Solder Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 500V Current Rating 10A	Number of Positions	4 (3 + PE)	
Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated500VCurrent Rating10A	Shell Size - Insert	12-4	
Termination Solder Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 500V Current Rating 10A	Shell Size, MIL	-	
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 500V Current Rating 10A	Mounting Type	Panel Mount, Flange; Through Hole	
Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 500V Current Rating 10A	Termination	Solder	
Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating 10A	Fastening Type	Bayonet Lock	
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating 10A Thermoplastic 10A	Orientation	N (Normal)	
Contact Finish Gold Features - Voltage - Rated 500V Current Rating 10A	Ingress Protection	IP68/69K - Dust Tight, Water Resistant, Waterproof	
Features - Voltage - Rated 500V Current Rating 10A	Shell Material, Finish	Thermoplastic	
Voltage - Rated 500V Current Rating 10A	Contact Finish	Gold	
Current Rating 10A	Features	-	
	Voltage - Rated	500V	
Report errors?	Current Rating	10A	
Report chois.		Report errors	?

UTS012D4S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UTS012D4S Payment Methods



















UTS012D4S Shipping Methods













If you have any question about UTS012D4S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com