



## **UTS014D12P Information**

Part Number UTS014D12P
Manufacturer Souriau

Category Connectors, Interconnects Circular Connectors

**Description** CONN RCPT 12POS PNL MNT PIN PCB

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **UTS014D12P Specifications**

Manufacturer Part Number     UTS014D12P       Manufacturer     Souriau       Category     Connectors, Interconnects       Package     -       Series     Trim Trio? UTS Hi Seal       Connector Type     Receptacle, Male Pins       Number of Positions     12       Shell Size - Insert     14-12       Shell Size, MIL     -       Mounting Type     Panel Mount, Flange; Through Hole       Termination     Solder       Fastening Type     Bayonet Lock       Orientation     N (Normal)       Ingress Protection     IP68/69K - Dust Tight, Water Resistant, Waterproof       Shell Material, Finish     Thermoplastic       Contact Finish     Gold       Features     -       Voltage - Rated     250V       Current Rating     4.5A		
Category Circular Connectors  Package - Series Trim Trio? UTS Hi Seal Connector Type Receptacle, Male Pins Number of Positions 12 Shell Size - Insert 14-12 Shell Size, MIL - Mounting Type Panel Mount, Flange; Through Hole Termination Solder Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated Current Rating  Connectors, Interconnects Circular Connectors  - Connectors Interconnectors Interco	Manufacturer Part Number	UTS014D12P
Package-SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Male PinsNumber of Positions12Shell Size - Insert14-12Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated250VCurrent Rating4.5A	Manufacturer	Souriau
Package - Connector Type Receptacle, Male Pins Number of Positions 12 Shell Size - Insert 14-12 Shell Size, MIL - Mounting Type Panel Mount, Flange; Through Hole Termination Solder Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Gold Features - Contact Finish Gold Current Rating 4.5A	Category	Connectors, Interconnects
SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Male PinsNumber of Positions12Shell Size - Insert14-12Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated250VCurrent Rating4.5A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions12Shell Size - Insert14-12Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated250VCurrent Rating4.5A	Package	-
Number of Positions12Shell Size - Insert14-12Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated250VCurrent Rating4.5A	Series	Trim Trio? UTS Hi Seal
Shell Size - Insert  Shell Size, MIL  Mounting Type  Panel Mount, Flange; Through Hole  Termination  Solder  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  IP68/69K - Dust Tight, Water Resistant, Waterproof  Shell Material, Finish  Thermoplastic  Contact Finish  Gold  Features  -  Voltage - Rated  250V  Current Rating  4.5A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange; Through Hole Termination Solder Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features Voltage - Rated 250V Current Rating 4.5A	Number of Positions	12
Mounting Type Panel Mount, Flange; Through Hole  Termination Solder  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof  Shell Material, Finish Thermoplastic  Contact Finish Gold  Features -  Voltage - Rated 250V  Current Rating 4.5A	Shell Size - Insert	14-12
Termination Solder Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 250V Current Rating 4.5A	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Contact Finish  Features  Voltage - Rated  Current Rating  Bayonet Lock  N (Normal)  IP68/69K - Dust Tight, Water Resistant, Waterproof  Thermoplastic  Contact Finish  Gold  -  Voltage - Rated  250V  4.5A	Mounting Type	Panel Mount, Flange; Through Hole
Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 250V Current Rating 4.5A	Termination	Solder
Ingress Protection  IP68/69K - Dust Tight, Water Resistant, Waterproof  Thermoplastic  Contact Finish  Gold  Features  Voltage - Rated  Current Rating  IP68/69K - Dust Tight, Water Resistant, Waterproof  Thermoplastic  250V  4.5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating 4.5A Thermoplastic  4.5A	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 250V Current Rating 4.5A	Ingress Protection	IP68/69K - Dust Tight, Water Resistant, Waterproof
Features - Voltage - Rated 250V Current Rating 4.5A	Shell Material, Finish	Thermoplastic
Voltage - Rated 250V Current Rating 4.5A	Contact Finish	Gold
Current Rating 4.5A	Features	-
	Voltage - Rated	250V
Report errors?	Current Rating	4.5A
		Report errors?

### **UTS014D12P Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **UTS014D12P Payment Methods**





















## **UTS014D12P Shipping Methods**













If you have any question about UTS014D12P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com