



UTS014D5S Information

Part Number UTS014D5S
Manufacturer Souriau

Category Connectors, Interconnects Circular Connectors

Description CONN RCPT 5POS PNL MNT SKT PCB

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UTS014D5S Specifications

| Manufacturer Part NumberUTS014D5SManufacturerSouriauCategoryConnectors, InterconnectsPackage-SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Female SocketsNumber of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGold | | |
|---|--------------------------|--|
| Category Connectors, Interconnects Circular Connectors Package - Series Trim Trio? UTS Hi Seal Connector Type Receptacle, Female Sockets Number of Positions 5 Shell Size - Insert 14-5 Shell Size, MIL - Mounting Type Panel Mount, Flange; Through Hole Termination Solder Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Termoplastic | Manufacturer Part Number | UTS014D5S |
| Circular ConnectorsPackage-SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Female SocketsNumber of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplastic | Manufacturer | Souriau |
| Package - Trim Trio? UTS Hi Seal Connector Type Receptacle, Female Sockets Number of Positions 5 Shell Size - Insert 14-5 Shell Size, MIL - Mounting Type Panel Mount, Flange; Through Hole Termination Solder Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic | Category | Connectors, Interconnects |
| Series Trim Trio? UTS Hi Seal Connector Type Receptacle, Female Sockets Number of Positions 5 Shell Size - Insert 14-5 Shell Size, MIL - Mounting Type Panel Mount, Flange; Through Hole Termination Solder Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic | | Circular Connectors |
| Connector Type Receptacle, Female Sockets Number of Positions 5 Shell Size - Insert 14-5 Shell Size, MIL - Mounting Type Panel Mount, Flange; Through Hole Termination Solder Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic | Package | - |
| Number of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplastic | Series | Trim Trio? UTS Hi Seal |
| Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange; Through Hole Termination Solder Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish | Connector Type | Receptacle, Female Sockets |
| Shell Size, MIL Mounting Type Panel Mount, Flange; Through Hole Termination Solder Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic | Number of Positions | 5 |
| Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplastic | Shell Size - Insert | 14-5 |
| Termination Solder Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic | Shell Size, MIL | - |
| Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic | Mounting Type | Panel Mount, Flange; Through Hole |
| Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic | Termination | Solder |
| Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplastic | Fastening Type | Bayonet Lock |
| Shell Material, Finish Thermoplastic | Orientation | N (Normal) |
| • | Ingress Protection | IP68/69K - Dust Tight, Water Resistant, Waterproof |
| Contact Finish Gold | Shell Material, Finish | Thermoplastic |
| | Contact Finish | Gold |
| Features - | Features | - |
| Voltage - Rated 650V | Voltage - Rated | 650V |
| Current Rating 12A | Current Rating | 12A |
| Report errors? | | Report errors? |

UTS014D5S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UTS014D5S Payment Methods



















UTS014D5S Shipping Methods













If you have any question about UTS014D5S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com