



### **UTS014E15P Information**

wv.w.l

Part Number UTS014E15P Manufacturer Souriau

Category Connectors, Interconnects Circular Connectors

**Description** CONN RCPT 15POS PNL MNT PIN SLDR

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **UTS014E15P Specifications**

Manufacturer Part Number         UTS014E15P           Manufacturer         Souriau           Category         Connectors, Interconnects           Package         -           Series         Trim Trio? UTS Hi Seal           Connector Type         Receptacle, Male Pins           Number of Positions         15           Shell Size - Insert         14-15           Shell Size, MIL         -           Mounting Type         Panel Mount, Flange           Termination         Solder Cup           Fastening Type         Bayonet Lock           Orientation         N (Normal)           Ingress Protection         IP68/69K - Dust Tight, Water Resistant, Waterproof           Shell Material, Finish         Thermoplastic           Contact Finish         Gold           Features         -           Voltage - Rated         650V           Current Rating         12A			
CategoryConnectors, InterconnectsPackage-SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Male PinsNumber of Positions15Shell Size - Insert14-15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated650VCurrent Rating12A	Manufacturer Part Number	UTS014E15P	
Package-SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Male PinsNumber of Positions15Shell Size - Insert14-15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated650VCurrent Rating12A	Manufacturer	Souriau	
Package-SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Male PinsNumber of Positions15Shell Size - Insert14-15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated650VCurrent Rating12A	Category	Connectors, Interconnects	
SeriesTrim Trio? UTS Hi SealConnector TypeReceptacle, Male PinsNumber of Positions15Shell Size - Insert14-15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated650VCurrent Rating12A		Circular Connectors	
Connector TypeReceptacle, Male PinsNumber of Positions15Shell Size - Insert14-15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated650VCurrent Rating12A	Package	-	
Number of Positions15Shell Size - Insert14-15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated650VCurrent Rating12A	Series	Trim Trio? UTS Hi Seal	
Shell Size - Insert14-15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated650VCurrent Rating12A	Connector Type	Receptacle, Male Pins	
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 650V Current Rating 12A	Number of Positions	15	
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeatures-Voltage - Rated650VCurrent Rating12A	Shell Size - Insert	14-15	
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 650V Current Rating 12A	Shell Size, MIL	-	
Fastening Type  Bayonet Lock Orientation  N (Normal)  Ingress Protection  IP68/69K - Dust Tight, Water Resistant, Waterproof  Thermoplastic  Contact Finish  Gold  Features  -  Voltage - Rated  650V  Current Rating  12A	Mounting Type	Panel Mount, Flange	
Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 650V Current Rating 12A	Termination	Solder Cup	
Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features - Voltage - Rated 650V Current Rating 12A	Fastening Type	Bayonet Lock	
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating 12A Thermoplastic Gold Cold Cold Cold Cold Cold Cold Cold C	Orientation	N (Normal)	
Contact Finish Gold Features - Voltage - Rated 650V Current Rating 12A	Ingress Protection	IP68/69K - Dust Tight, Water Resistant, Waterproof	
Features - Voltage - Rated 650V Current Rating 12A	Shell Material, Finish	Thermoplastic	
Voltage - Rated 650V Current Rating 12A	Contact Finish	Gold	
Current Rating 12A	Features	-	
-	Voltage - Rated	650V	
Report errors?	Current Rating	12A	
		Report error	s?

#### **UTS014E15P Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **UTS014E15P Payment Methods**





















### **UTS014E15P Shipping Methods**













If you have any question about UTS014E15P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com