



UTS6FC12E2S Information

Part Number UTS6FC12E2S

Manufacturer Souriau

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 2POS CABLE SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UTS6FC12E2S Specifications

Manufacturer Part Number UTS6FC12E2S Manufacturer Souriau Category Connectors, Interconnects Package - Series Trim Trio? UTS Hi Seal Connector Type Plug, Female Sockets Number of Positions 2 Shell Size - Insert 12-2 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polyamide (PA), Nylon Contact Finish Gold Features Backshell Voltage - Rated 650V Current Rating 13A			
CategoryConnectors, InterconnectsPackage-SeriesTrim Trio? UTS Hi SealConnector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert12-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolyamide (PA), NylonContact FinishGoldFeaturesBackshellVoltage - Rated650VCurrent Rating13A	Manufacturer Part Number	UTS6FC12E2S	
Package-SeriesTrim Trio? UTS Hi SealConnector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert12-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolyamide (PA), NylonContact FinishGoldFeaturesBackshellVoltage - Rated650VCurrent Rating13A	Manufacturer	Souriau	
Package-SeriesTrim Trio? UTS Hi SealConnector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert12-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolyamide (PA), NylonContact FinishGoldFeaturesBackshellVoltage - Rated650VCurrent Rating13A	Category	Connectors, Interconnects	
SeriesTrim Trio? UTS Hi SealConnector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert12-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolyamide (PA), NylonContact FinishGoldFeaturesBackshellVoltage - Rated650VCurrent Rating13A		Circular Connectors	
Connector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert12-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolyamide (PA), NylonContact FinishGoldFeaturesBackshellVoltage - Rated650VCurrent Rating13A	Package	-	
Number of Positions2Shell Size - Insert12-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolyamide (PA), NylonContact FinishGoldFeaturesBackshellVoltage - Rated650VCurrent Rating13A	Series	Trim Trio? UTS Hi Seal	
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polyamide (PA), Nylon Contact Finish Gold Features Backshell Voltage - Rated 650V Current Rating 13A	Connector Type	Plug, Female Sockets	
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polyamide (PA), Nylon Contact Finish Gold Features Backshell Voltage - Rated 650V Current Rating 13A	Number of Positions	2	
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolyamide (PA), NylonContact FinishGoldFeaturesBackshellVoltage - Rated650VCurrent Rating13A	Shell Size - Insert	12-2	
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polyamide (PA), Nylon Contact Finish Gold Features Backshell Voltage - Rated 650V Current Rating 13A	Shell Size, MIL	-	
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polyamide (PA), Nylon Contact Finish Gold Features Backshell Voltage - Rated 650V Current Rating 13A	Mounting Type	Free Hanging (In-Line)	
Orientation N (Normal) Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polyamide (PA), Nylon Contact Finish Gold Features Backshell Voltage - Rated 650V Current Rating 13A	Termination	Solder Cup	
Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Contact Finish Gold Features Backshell Voltage - Rated Current Rating 13A	Fastening Type	Bayonet Lock	
Shell Material, Finish Polyamide (PA), Nylon Contact Finish Gold Features Backshell Voltage - Rated 650V Current Rating 13A	Orientation	N (Normal)	
Contact Finish Gold Features Backshell Voltage - Rated 650V Current Rating 13A	Ingress Protection	IP68/69K - Dust Tight, Water Resistant, Waterproof	
Features Backshell Voltage - Rated 650V Current Rating 13A	Shell Material, Finish	Polyamide (PA), Nylon	
Voltage - Rated 650V Current Rating 13A	Contact Finish	Gold	
Current Rating 13A	Features	Backshell	
	Voltage - Rated	650V	
Report errors?	Current Rating	13A	
		Report error	s?

UTS6FC12E2S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UTS6FC12E2S Payment Methods



















UTS6FC12E2S Shipping Methods













If you have any question about UTS6FC12E2S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com